

Secvest Hybrid Module Set Power Supply

Art.-Nr. FUM050200

Seite 1 von 3



Technical data - Secvest Hybrid Module Set Power Supply

Dimensions	460x360x350 mm
Gross weight	7,27 kg
Height	350 mm
Length	460 mm
Net weight	7,07 kg
PSTI conformity required	No
Width	360 mm

Technical data - Secvest Hybrid Module

DC voltage supply	10,5 - 15 V
Dimensions	(LxWxH) 136x227x45 mm
Environmental class	II
Gross weight	0,62 kg
Height	45 mm
Housing material	PC/ABS
IP protection class	30
Installation type	Surface mounted
Language of instructions	DE,EN,FR,NL,DK,IT
Length	227 mm
Max. humidity	75 %
Max. operating temperature	40 °C
Max. receiving range (free field)	500 m
Max. transmission range (free field)	500 m

Secvest Hybrid Module Set Power Supply

Art.-Nr. FUM050200

Seite 2 von 3

Technical data - Secvest Hybrid Module

Min. operating temperature	-10 °C
Net weight	0,48 kg
Number of wired zones	10 x FSL/DEOL or 5 x CC
Outputs	4 x Relays (max. 24 V AC rms or 30 V DC)
PSTI conformity required	No
Power consumption	100 mA
Programming	Directly at the alarm control panel or via web server
Radio frequency	868,6625 MHz
Radio power	10 mW
Sabotage monitoring	Yes
Transmission path	Wireless
Type of inputs	Voltage
Voltage monitoring	Yes
Width	136 mm
EAN	4043158144635

Technical data - CCTV Performance Power Supply 2 A

AC voltage supply	230 V
Charging electronics	12 / 7 V/Ah
Dimensions	(W x H x D) 338 x 281 x 86 mm
Emergency battery	BT2070 (optional)
Fuse protection outputs	8 x F2.0 A, 20 mm
Height	281 mm
Housing material	metal
Length	86 mm
Material type	Metal housing
Net weight	3,26 kg
Output	8
Output voltage DC	13,4 – 14,2 on main supply / 10,0 – 12,3 battery supply V
PSTI conformity required	No
Sabotage monitoring	Cover switch
Width	338 mm
EAN	4043158025484

Technical data - VdS Battery, 12 V, 7.2 Ah

Battery type	Lead gel
Capacity	7,2
Certifications	VdS
Charging cycles	up to 1000
DC voltage supply	12 V

Secvest Hybrid Module Set Power Supply



Security Tech Germany

Art.-Nr. FUM050200

Seite 3 von 3

Technical data - VdS Battery, 12 V, 7.2 Ah

Dimensions	(WxHxD) 65x94x151 mm
Height	94 mm
Length	151 mm
Net weight	2,54 kg
PSTI conformity required	No
VdS approval no.	G 112110
Width	65 mm
EAN	4043158000634