

Secvest Hybrid module Set magnetic contact

Art.-Nr. FUM050220

Seite 1 von 4

Starter package including five opening detectors

For securing additional windows and doors. For efficient expansion of the Secvest wireless alarm system with wired alarm detectors via the hybrid module.

Secvest plus hybrid module: more range and applications

By radio integration of a module, the Secvest can be extended by 10 wire zones and four relay outputs. A maximum of two modules can be integrated per control panel. This means that detectors (20xFSL or 10xCC) and components for extensions or new buildings can be integrated, larger distances can be bridged and new object sizes can be realized. Conversely, wired alarm detectors can be integrated into the Secvest via the hybrid module.

Networking and home automation

The hybrid module allows the integration of the ABUS wAppLoxx independent of the installation location of the control panel. In addition, ABUS IP cameras can be integrated via the WLX Control or the Secvest control panel. The four additional relay outputs also enable numerous applications from the field of home control. For example, the operation of the garage door, the house lighting or shutter control.

Technical data - Secvest Hybrid module Set magnetic contact

Cable length	4 m
Colour	white
Dimensions	310x220x160 mm
EN	Level 2
Gross weight	1.303 kg
Height	160 mm
Length	310 mm
Mechanical protection	No
Net weight	1.076 kg
PSTI conformity needed	No
Product group	Extension
Radio networked	No
VdS class	sonstige
WEEE group	19
Width sensor	11 mm
width	220 mm

Secvest Hybrid module Set magnetic contact

Art.-Nr. FUM050220

Seite 2 von 4

Technical data - Opening Detector, 4 m, 4-core (white)

Cable length	4 m
Cable style	4-core
Certifications	VdS B, EN 50131 Grade 2, VSÖ GS-N
Colour	weiß
Compatible with	Secoris, Secvest, Terxon
Connections	NC, max. contact capacity 24 V DC / AC / 0.2 A / 4.8 W
Detection method	Magnetic field measurement
Dimensions	(WxHxD) 11x12x48 mm
EN	Grade 2
Environmental class	IIIa
External field protection	No
Height	12 mm
Housing material	ABS
Length	48 mm
Max. Operating temperature	55 °C
Mechanical protection	No
Min. operating temperature	-40 °C
Mounting location	Integration / surface mounting
Mounting type	Surface mounting/recessed mounting
Net weight	0.082 kg
PSTI conformity needed	No
Product group	Detectors
Radio networked	No
Sensor type	Reed contact
Tamper monitoring	Yes
Type of protection	Intrusion protection
VdS approval no.	G 105519
VdS class	B
WEEE group	09
Width sensor	11 mm
width	11 mm
EAN	4043158001228

Technical data - Secvest Hybrid Module

Current consumption	100 mA
DC power supply	10,5 - 15 V
Dimensions	(LxWxH) 136x227x45 mm
EN	Level 2
Environmental class	II
Gross weight	0.62 kg

Secvest Hybrid module Set magnetic contact

Art.-Nr. FUM050220

Seite 3 von 4

Technical data - Secvest Hybrid Module

Height	45 mm
Housing material	PC/ABS
Language Manual	DE,EN,FR,NL,DK,IT
Length	227 mm
Max. Air humidity	75 %
Max. Operating temperature	40 °C
Max. Receive range (free field)	500 m
Max. Transmit range (free field)	500 m
Mechanical protection	No
Min. operating temperature	-10 °C
Mounting type	Surface mounted
Net weight	0.491 kg
Number of wire zones	10 x FSL/DEOL or 5 x CC
Outputs	4 x Relays (max. 24 V AC rms or 30 V DC)
PSTI conformity needed	No
Programming 1	Directly at the alarm control panel or via web server
Protection class IP	30
Radio frequency	868.6625 MHz
Radio power	10 mW
Tamper monitoring	Yes
Transmission path	Wireless
Type of inputs	Voltage
Voltage monitoring	Yes
WEEE group	09
width	136 mm
EAN	4043158144635

Technical data - International Switching-Mode Power Supply 13,8 V/1,75 A (Cord)

AC power supply	100 - 240 V
Cable length	1.5 m
Current consumption	1.75 mA
DC power supply	13,8 V
Dimensions	(W x H x D) about 46 x 80 x 38 mm
Housing material	ABS (white)
Input voltage AC	230 V
Max. Air humidity	90 %
Max. Operating temperature	40 °C
Min. operating temperature	0 °C
Net weight	0.175 kg

Secvest Hybrid module Set magnetic contact

Art.-Nr. FUM050220

Seite 4 von 4

Technical data - International Switching-Mode Power Supply 13,8 V/1,75 A (Cord)

Output voltage DC	13,8 V
PSTI conformity needed	No
Product group	Accessories
WEEE group	09
EAN	4043158067521