

# IP Tube 8 MPx Black (2.8 - 12mm)

Art.-Nr. IPCB68621

Seite 1 von 4



## BRILLIANT OUTSIDE: IN ANY LIGHT. AGAINST MANIPULATION.

With 8 MPx resolution, weatherproof IP67 housing in black (ABUS Black Line), IK10 vandal protection and powerful IR LEDs, the IP Tube is the surveillance camera for 24/7 outdoor surveillance day and night. WDR dynamics and Ultra Low-Light ensure clear images in any light.

## Flexible monitoring in 4K Ultra HD

The motorised zoom lens with 2.8-12 mm focal length covers a range of 46-108° (4.2x optical). Focal length and focus are precisely adjusted via the web interface, and the viewing direction is easily fixed with a single screw.

## Autom. Object recognition

The security camera reliably distinguishes relevant movements (people, vehicles) from disturbances (branches, light, etc.) and thus minimises unnecessary motion alarms.

## Recording and compatibility

Recordings are made on an ABUS recorder, on video management software or local microSD card. The camera is compatible with ABUS Secvest, Secoris and WLX Pro Plus.

## Convenient start-up

The installation box (TVAC32600X) is used for mounting on the ceiling or wall with protected cabling. The free ABUS IP Installer software makes setup easier.

## ABUS Link Station app: Live Image & Push

For mobile access for live viewing, playback and push notifications for events, incl. IPv6.

Notes: No power supply unit is included, as power is supplied via PoE.

# IP Tube 8 MPx Black (2.8 - 12mm)

Art.-Nr. IPCB68621

Seite 2 von 4

The effective IR range will vary depending on the installation location.

## Technologies

- 8 MPx (4K) resolution: 3,840 x 2,160 @ 20 fps for accurate, detailed surveillance of large areas and grounds
- 2.8 - 12 mm motorised zoom lens (4x optical zoom, 46°-108° viewing angle) for high flexibility in surveillance and choice of installation location, incl. easy setup of focal length, focus and viewing direction
- Ultra low-light performance for excellent image results in poorly lit environments
- 120 dB WDR function to compensate for image contrasts, strong backlighting etc.
- Object recognition (human & vehicle): Motion detection with fully automatic differentiation between people/vehicles and disturbances (branches, light, etc.)
- Very robust, vandalism- and weather-proof housing (IK10 & IP67); colour: black
- IR LEDs for very clear images in the dark (up to 60 m range)
- Supports H.264, H.265, MJPEG (incl. Dynamic GOP)
- MicroSD card slot for internal data storage
- 12 V DC & PoE (802.3at)

## Technical data - IP Tube 8 MPx Black (2.8 - 12mm)

Alarm input (NO/NC)	1
Alarm output	1
Alarming	E-Mail, NAS, FTP, Sound
Aperture at minimum illumination (colour)	F1.4
Audio	Connectable: Microphone, Loudspeaker
Backlight compensation	WDR, BLC, HLC
Camera type	Tube
Colour	Black
Compatible with	ABUS NVR, ABUS Link Station App, Synology Surveillance Station 6.0.1+
Compatible with ABUS Link Station	Yes
Compatible with Comfion	Yes
Compatible with Secoris	Yes
Compatible with Secvest	Yes
Compatible with wAppLoxx	Yes
Compatible with wAppLoxx Pro	Yes
Connections	1 x RJ45, 1 x DC, 1 x Alarm input, 1 x Alarm output, 1 x Audio input, 1 x Audio output, 1 x Video output
DC voltage supply	12 (+/-25 %) V
Day/night switching	ICR/Color/B/W

# IP Tube 8 MPx Black (2.8 - 12mm)

Art.-Nr. IPCB68621

Seite 3 von 4

## Technical data - IP Tube 8 MPx Black (2.8 - 12mm)

Design	Tube
Digital zoom	Yes
Dimensions	(LxWxH) 298x105x105 mm
Dynamic range (WDR)	120 dB
Electronic shutter	1/3 - 1/1000000 s
Encryption	HTTPS, TLS 1.1/1.2
Focal length	2,8 – 12,0 mm
Frame rate	1/16, 1/8, 1/4, 1/2, 1, 2, 4, 6, 8, 10, 12, 15, 16, 18, 20, 22, 25, 30 fps
Functions	Scene Change Detection, Region of Interest
Gross weight	2,1 kg
Height	105 mm
Horizontal viewing angle	46 – 108 °
Housing material	Metal
ICR day/night function	Yes
IP protection class	67
IR LEDs	Yes
IR range (up to)	60 m
Image enhancement	WDR, BLC, HLC, 3D DNR
Image sensor	1/1.8" Progressive Scan CMOS
Installation type	Ceiling, Wall
LAN network access	RJ45 10M/100M self-adaptive
Language of instructions	DE, UK, FR, NL, DK
Length	298 mm
Lens	Motor-Zoom
Max. humidity	95 %
Max. operating temperature	60 °C
Max. resolution @ frame rate	3840 x 2160 @ 25 fps
Microphone	No
Min. operating temperature	-25 °C
Minimum illumination (IR)	0 lx
Minimum illumination (colour)	0,003 lx
Motion detection	8 zones
Net weight	1,4 kg
Network camera protocols	IPv4/v6, HTTP, HTTPS, FTP, SMTP, UPnP, DNS, DynDNS, NTP, RTSP, TCP, UDP, DHCP, ABUS Server, P2P, QoS, 802.1X, IGMP, Bonjour, PPPoE, SNMP
Noise reduction	3D DNR
Number of IR LEDs	4
Number of streams	3

# IP Tube 8 MPx Black (2.8 - 12mm)

Art.-Nr. IPCB68621

Seite 4 von 4

## Technical data - IP Tube 8 MPx Black (2.8 - 12mm)

Number of users	32
ONVIF	Profile G, S, T
OSD language	DE, UK, FR, NL, DK, IT
Optical zoom	4,2 x
Other functions	Object Classification Person/Vehicle
PSTI conformity given	Yes
PSTI conformity required	Yes
Pixels (effective)	3840(H) x 2160(V) pixel
PoE standard	IEEE 802.3at
Power consumption	1.350 mA
Private zones	4
Protection class IK	10
Resolution	8 MP
Resolution modes	Stream 1: 3840 x 2160 @ 25 fps, Stream 2: 640 x 480 @ 30 fps, Stream 3: 1280 x 720 @ 30 fps
Storage medium	microSD card, 256 GB (opt.)
Supported browsers	IE11, Mozilla Firefox, Google Chrome, MS Edge
Technology	IP
Vertical viewing angle	26 – 58 °
Video Content Analysis (VCA)	Tripwire Detection, Intrusion Detection, Region Entrance, Region Exit
Video compression	Stream 1: H.264, H.265, Dynamic GOP (+), Stream 2: H.264, H.265, MJPEG, Stream 3: H.264, H.265
Video network bandwidth	32 kBit/s - 16 MBit/s
White balance	AWB, Manual
Width	105 mm