

IP Mini Tube 4 MPx (2.8 mm, WL)

Art.-Nr. IPCS34511A

Seite 1 von 4



SMALL CAMERA, BIG DETAILS AT NIGHT

This IP Mini Tube is a compact LAN camera with full colour day/night function and delivers images in 4 MPx resolution. With its white light LEDs in IP67 housing, it is designed for indoor/outdoor use by day and night. Mobile access to the camera via ABUS Link Station app.

Discreet surveillance: strong in the dark

Clear colour images in total darkness thanks to full-colour day/night technology - rich in detail for solid evidence. The slightest residual light is effectively amplified by the special lens and the extra light-sensitive image sensor. The white light LEDs provide a touch of extra light for the image sensor, barely visible to the eye.

2 variants for max. flexibility

The camera is available with 2 focal lengths: 2.8 mm / 108° field of view (IPCS34511A) and 4 mm / 95° (IPCS34511B).

Autom. Object recognition

The security camera distinguishes relevant movements (people, vehicles) from interferences (branches, light, etc.) - and minimises unnecessary motion alarms.

Recording and compatibility

Recording is done on ABUS NVR, VMS or microSD card. The camera is compatible with ABUS Secvest, Secoris and WLX Pro.

Quick start-up

Mounting with protected cable via installation box (TVAC32600). The ABUS IP Installer software simplifies the setup in the network.

Notes: Without power supply unit, because PoE.

IP Mini Tube 4 MPx (2.8 mm, WL)

Art.-Nr. IPCS34511A

Seite 2 von 4

The effective LED range varies depending on the location.

Technologies

- 4 MPx resolution (2,688 x 1,520 @ 25 fps) for crisp surveillance images
- 2.8 mm fixed-focus lens for a good overview (108° field of view)
- Detailed, highly usable colour images in the dark thanks to full-colour day/night technology; effectively amplifies even minimal ambient light using a special lens and very light-sensitive image sensor
- Discreet illumination of the field of view with white-light LEDs (up to 30 m range) for accurate colour images in total darkness (e.g. indoors); touch of illumination for the light-sensitive image sensor (barely visible to the human eye)
- Object recognition (human & vehicle): Video content analysis with fully automatic differentiation between people/vehicles and interferences (branches, light, etc.)
- Optional output of 3 video streams in ideal resolution for, e.g., live image, recording, mobile access, etc.
- Sturdy, weatherproof housing (IP67)
- Supports H.264, H.265, MJPEG (incl. Dynamic GOP)
- microSD card slot for internal data storage, encrypted for high data security (optional)
- 12 V DC & PoE (802.3af)

Technical data - IP Mini Tube 4 MPx (2.8 mm, WL)

Additional functions	White light range up to 30 m
Alarming	E-Mail, NAS, FTP
Aperture at minimum illumination (colour)	F1.0
Audio	Integrated: Microphone
Backlight compensation	WDR, BLC, HLC
Camera type	Mini Tube
Compatible with	ABUS NVR/DVR, ABUS Link Station App, Synology Surveillance Station 6.0.1+
Compatible with ABUS Link Station	Yes
Compatible with Comfion	Yes
Compatible with Secoris	Yes
Compatible with Secvest	Yes
Compatible with wAppLoxx	Yes
Compatible with wAppLoxx Pro	Yes
Connections	1 x RJ45, 1 x DC
DC voltage supply	12 (+/-25 %) V
Design	Mini Tube
Digital zoom	Yes

IP Mini Tube 4 MPx (2.8 mm, WL)

Art.-Nr. IPCS34511A

Seite 3 von 4

Technical data - IP Mini Tube 4 MPx (2.8 mm, WL)

Dimensions	(LxWxH) 223x85x85 mm
Dynamic range (WDR)	120 dB
Electronic shutter	1/3 - 1/1000000 s
Encryption	HTTPS, TLS 1.1/1.2
Focal length	2,8 mm
Frame rate	1/16, 1/8, 1/4, 1/2, 1, 2, 4, 6, 8, 10, 12, 15, 16, 18, 20, 22, 25, 30 fps
Functions	Scene Change Detection, Region of Interest
Gross weight	0,7 kg
Height	85 mm
Horizontal viewing angle	108 °
Housing material	Metal
IP protection class	67
Image enhancement	WDR, BLC, HLC, 3D DNR, Vertical Display (not in Smart-Event mode)
Image integration	Yes
Image sensor	1/1.8" Progressive Scan CMOS
Installation type	Ceiling, Wall
LAN network access	RJ45 10M/100M self-adaptive
Language of instructions	DE, UK, FR, NL, DK
Length	223 mm
Lens	Fix
Max. humidity	95 %
Max. operating temperature	60 °C
Max. resolution @ frame rate	2688 x 1520 @ 30 fps
Microphone	Yes
Min. operating temperature	-25 °C
Minimum illumination (colour)	0,0005 lx
Motion detection	8 zones
Net weight	0,5 kg
Network camera protocols	IPv4/v6, HTTP, HTTPS, FTP, SMTP, UPnP, DNS, DynDNS, NTP, RTSP, TCP, UDP, DHCP, ABUS Server, P2P, QoS, 802.1X, IGMP, Bonjour, PPPoE, SNMP
Noise reduction	3D DNR
Number of streams	3
Number of users	32
OSD language	DE, UK, FR, NL, DK, IT
Other functions	Object Classification Person/Vehicle
PSTI conformity given	Yes
PSTI conformity required	Yes
Pixels (effective)	2688(H) x 1520(V) pixel

IP Mini Tube 4 MPx (2.8 mm, WL)

Art.-Nr. IPCS34511A

Seite 4 von 4

Technical data - IP Mini Tube 4 MPx (2.8 mm, WL)

PoE standard	IEEE 802.3af
Power consumption	600 mA
Private zones	4
Resolution	4 MP
Resolution modes	Stream 1: 2688 x 1520 @ 25 fps, Stream 2: 640 x 480 @ 25 fps, Stream 3: 1920 x 1080 @ 10 fps
Storage medium	microSD card, 256 GB (opt.)
Supported browsers	IE11, Mozilla Firefox, Google Chrome, MS Edge
Technology	IP
Vertical viewing angle	55 °
Video Content Analysis (VCA)	Tripwire Detection, Intrusion Detection, Region Entrance, Region Exit
Video compression	Stream 1: H.264, H.265, Dynamic GOP (+), Stream 2: H.264, H.265, MJPEG, Stream 3: H.264, H.265
Video network bandwidth	32 kBit/s - 8 MBit/s
White balance	AWB, Manual
White-light LEDs	2
White-light range (up to)	30 m
Width	85 mm