

# SRG92N for tubular frame doors in stainless steel look (Door handle on both sides)

Seite 1 von 2



## Technologies

- Distance of cams adjustable to most common drilling patterns
- Handle on inside automatically returns to initial position
- Fixing screws hidden by decorative aluminium plate
- For cylinder protrusions of 12 mm
- Spacing: 92 mm, square bolt: 8 mm
- Easy fitting

## Operation and use

- For universal use on narrow frames
- Grip plate outside, handle inside
- Suitable for door thicknesses of 57 - 65 mm

## Variants

- Finishes: F1 (alu anodized), F2 (silver anodized), stainless steel look, white
- Alternatively available as a handle/handle set

## Technical data - SRG92N for tubular frame doors in stainless steel look (Door handle on both sides)

Beidseitig Drücker	Yes
Cylinder protrusion	12 mm
Distance measure	92 mm
Door fitting for fire doors	No
Door type	Doors with tubular frames
Interchangeable fitting	No
Security Level Home Security	5

# SRG92N for tubular frame doors in stainless steel look (Door handle on both sides)

Seite 2 von 2

## Technical data - SRG92N for tubular frame doors in stainless steel look (Door handle on both sides)

Weight	1037 g
colour	Stainless steel look
pulling protection	No
EAN	4003318625534

