

Secvest 2WAY Wireless Key Switch

Art.-Nr. FU8165

Seite 1 von 2



The Secvest 2WAY wireless key switch is an optional module for the Secvest 2WAY. It allows you to conveniently arm and disarm your alarm system simply by turning a key. Due to the modern design, the wireless key switch can be integrated perfectly into any entrance area. No more forgetting your code with the wireless key switch: This component of the Secvest family replaces entering a code at the alarm panel or at the control unit by the simple turn of a key. Two integrated LED display the status of the system. This avoids false alarms caused by wrong operation. Communication between the center and its components takes place on 868.6625 MHz - a radio frequency which is exclusively reserved for security purposes. The latest FM radio technology with millions of codes and duplex antenna technology guarantees reliable transmission of the signals. Protection class IP55 lets you also use the wireless key switch in protected outdoor areas.

Technologies

- Simple to install and operate
- Rugged housing
- Pull protection
- Sturdy housing
- Cylinder guard

Technical data - Secvest 2WAY Wireless Key Switch

Battery - max. battery life	2 y
Battery - type	3.6 V AA Li battery (FU2992) or 12 V DC
DC voltage supply	3,6/12 V
Dimensions	(WxHxD) 87x117x47 mm
Environmental class	II
Height	117 mm
Housing material	Aluminium and plastic

Secvest 2WAY Wireless Key Switch

Art.-Nr. FU8165

Seite 2 von 2

Technical data - Secvest 2WAY Wireless Key Switch

IP protection class	55
Installation location	Indoors and protected outdoor areas
Length	47 mm
Max. operating temperature	55 °C
Max. receiving range (building)	30 m
Max. receiving range (free field)	100 m
Max. transmission range (building)	30 m
Max. transmission range (free field)	100 m
Min. operating temperature	-10 °C
Net weight	0,55 kg
Power consumption	36 mA
Radio frequency	868,6625 MHz
Radio power	10 mW
Sabotage monitoring	1
Status display	1
Voltage monitoring	Yes
Width	87 mm