

# 4-channel analog HD video recorder

Art.-Nr. HDCC90002

Seite 1 von 3



Simple installation following the plug & play principle

The ABUS designed 4-Channel Analogue HD Video Recorder ensures that every recording solution is ready to use straight away - whether it be a retrofitting or a new project set-up with analogue HD technology. Video images can be provided in real-time and for recording as soon as the connection between the camera and recorder is set up using a coaxial or 2-wire connection (accessory: 2-Wire Analogue HD Transmission Set).

Storage space is doubled thanks to data compression

The compression of the incoming image data using H.265 technology uses storage space twice as efficiently. Up to 10 TB hard disk drive capacity can be installed, ensuring sufficient storage capacity is made available for sustained recording and any application.

Very easy and intuitive operation

Various modes of operation are available with the analogue HD recorder. The video data can be evaluated using a local monitor, browser, the intuitive ABUS CMS software or via the ABUS Link Station App for Android/iOS.

Automatic object detection

The recorder reliably distinguishes relevant movements (people, vehicles) from disruptive influences (twigs, light, etc.) - and minimizes the number of unnecessary movement alarms.

Pentaplex support

Supports TVI (max 5 MPx), CVI (max 1080p), AHD, CVBS (PAL / NTSC) signals on all BNC inputs

Support of two additional IP channels up to max. 6 MPx

Compatible with ABUS IP cameras. See compatibility list in the download area.

## Technologies

- Fanless and silent
- Pentaplex support: recording and live display of all channels up to 8 MPx (selected ABUS IP cameras, TVI, CVI, AHD, CVBS)
- Use storage space twice as efficiently: Data compression with H.265
- Ideal for retrofitting of existing systems to a higher resolution
- Long cable lengths up to a maximum of 500 m
- Object recognition (human & vehicle): Motion detection with fully automatic differentiation between

# 4-channel analog HD video recorder

Art.-Nr. HDCC90002

Seite 2 von 3

people/vehicles and disturbances (branches, light, etc.)

- Easy to operate: can be controlled via local monitor, Browser, app or ABUS CMS software
- Support for max. 2 IP cameras
- Permanent recording: 1x HDD up to 10TB

## Technical data - 4-channel analog HD video recorder

AC voltage supply	100 - 240 V
Alarm inputs (NO/NC)	4
Alarming	Acoustic warning, OSD signal, email
Analogue video channels	4
Audio	Line In: 4 x RCA (2,0 V p-p, 1000 $\Omega$ ), Audio Out: 1 x RCA (1000 $\Omega$ )
Audio bitrate	64 kbit/s
Audio compression	G.711u
Battery - GRS type	CR1220 / AAA
Battery - type	CR1220 / AAA
Camera inputs	4 x BNC (HD-TVI, HD-CVI, AHD, Analog CVBS)
Camera outputs	1 x BNC (Analog CVBS)
Control	Mouse, PC software, integrated web server
DDNS	Yes
Dimensions	380 x 320 x 48 mm
HD-SDI video channels	0
HD-TVI video channels	4
HDMI Out	Yes
Height	48 mm
IP video channels	2
Language of instructions	Deutsch, Englisch, Französisch, Niederländisch, Dänisch, Italienisch
Length	320 mm
Loi Sarkozy compliant (only valid for FR)	Yes
Max. humidity	90 %
Max. operating temperature	55 °C
Min. operating temperature	-10 °C
Mobile access	ABUS Link Station Lite / Pro (Apple iOS & Android)
Monitor outputs	1 x HDMI, 1 x VGA, 1 x Main BNC
NTP	Yes
Net weight	1,16 kg
Network access	1 x RJ45 10/100/1000 Mbps
Network cameras	See compatibility list in the download area
Network functions	DVR: NAS saving, IP-SAN saving/recorder software: Live view, playback, data export/web interface: Live view, playback, data export, log files, settings/apps: Live view, playback

# 4-channel analog HD video recorder

Art.-Nr. HDCC90002

Seite 3 von 3

## Technical data - 4-channel analog HD video recorder

Network protocols	TCP/IP, PPoE, DHCP, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP, HTTPS
Number of HDDs	1
OSD language	Deutsch, Englisch, Französisch, Niederländisch, Dänisch, Italienisch
Operating mode	Triplex
PSTI conformity given	Yes
PSTI conformity required	Yes
PTZ control	Coax
Power consumption	10 W
Pre/post alarm memory	0-2 / 5-900
Recording bitrate	32 Kbit/s up to 10 Mbit/s
Recording modes	VCA (tripwire, intrusion detection), motion detection, alarm, motion detection and alarm, motion detection or alarm, time schedule, manual
Recording resolution @ frame rate per camera	2MPx @ 25 frames/s, 3MPx @ 18 frames/s
Relay output	1
Resolution HDMI output	1920 x 1080 / 60 Hz, 1280 x 1024 / 60 Hz, 1280 x 720 / 60 Hz, 1024 x 768 / 60 Hz
Sabotage monitoring video	Yes
Search modes	Smart search, VCA, event, date & time
Simultaneous network access	32 channels
Software	ABUS CMS software
Storage	2 x USB 2.0
Storage medium	1 x SATA HDD (max. 10 TB)
Technology	AHD, CVBS, HD-CVI, HD-TVI, IP
Total frame rate (PAL)	100 fps
Total network throughput (input/output)	96Mbit (0 Mbit/96 Mbit)
Total video channels	6
User levels	2
Video compression	H.265
Views	1 / 4
Watchdog hardware	Yes
Web server	Yes
Width	380 mm