



It couldn't be simpler

Are you looking for a security camera that works without internet, Wi-Fi, computer and mobile phone? Ready to go in seconds and extremely easy to use? Then the ABUS EasyLook BasicSet is just right for you.

The set consists of a surveillance camera and a flexible, compact 7-inch monitor. It provides reliable video surveillance day and night and performs its job without internet/Wi-Fi, without an app and without separate devices like a smartphone. A practical solution for young and old, because both set components only need power; the video data and settings are securely encrypted and quickly transmitted wirelessly. The set can be expanded to up to 4 cameras at any time.

Is an unwanted intruder on the loose, or is it just a parcel delivery at the door? The camera's clever motion detection reliably detects people and animals. The monitor then gives a signal and shows you right what is happening. Simply tap the screen - and you can talk back via the camera, so that if in doubt, you can keep the front door closed. And what's more: The camera ignores unimportant movements of leaves in the wind, for example, or the heat radiation of heaters.

If necessary, use the monitor wirelessly for a short time and place it where it is needed. Also extremely practical: The set is ready to go in seconds - simply switch on the camera and monitor - and the first live image can be seen. Afterwards, it is just as easy to make a few personal settings via the monitor.

Technologies

- Wireless set of surveillance camera and portable monitor with touch screen; high range, reliable motion detection, alarm and recording mode, intercom function, night vision, privacy zone masking and much more
- Very easy to use without extra devices, without internet/Wi-Fi (power the camera, switch on the monitor, after a few seconds you can see the first live image; easy-to-understand user menu for personal settings)
- Inside and outside, the security camera reliably detects people/animals thanks to its clever motion detection

(integrated motion detector/passive infrared sensor, PIR for short, detects heat; camera software analyses for motion in parallel)

- Monitor immediately and automatically switches to alarm and recording mode (siren sound on the monitor can be switched on/off as required; insert standard microSD card with up to 128 GB for storage)
- Flexible monitor with high-quality, capacitive 7-inch colour display; for displaying live images and recordings (approx. 2 hours in battery mode if required) and for intercom (2-way audio through loudspeaker and microphone)
- Personal settings via touchscreen; deactivate audio/sound for recordings (GDPR/data protection compliant), image areas with/without recognition, schedules, privacy zones
- Clear night vision in black and white (via infrared LED) up to 15 metres, 3-megapixel camera resolution, zoom function, 82-degree viewing angle, camera protection class IP66 (weatherproof; protection against strong jets of water, dustproof)
- Can be expanded at any time to a total of 4 cameras (additional camera for ABUS EasyLook BasicSet)
- No further costs (no subscription, no cloud)

Technical data - ABUS EasyLook BasicSet

Area of application	Outdoor use
Functions	Intercom (2-way audio), Night vision, People recognition, Zoom
Power supply	Power adapter
System	Stand-alone

Technical data - ABUS EasyLook Monitor

Alarming	Acoustic warning signal
Battery - battery operation	Yes
Battery - quantity	2
Battery - runtime	Up to 2 hours
Battery - type	5200mAh rechargeable Battery
Channel width	20/40 MHz
Colour	Black
Compatible with Secvest	No
Compatible with Smartvest	No
Compatible with wAppLoxx	No
Connections	Power: DC plug / USB 2.0
DC voltage supply	12 V
Dimensions	(W x L x H) 199 x 32 x 123 mm
Encryption	WPA2
Frequency range	2,403 - 2,478 GHz
Housing material	Plastic
Loudspeaker	Yes
Max. operating temperature	40 °C
Microphone	Yes

Technical data - ABUS EasyLook Monitor

Min. operating temperature	0 °C
Modulation	DSSS , OFDM
Monitor type	7" Capacitive Touchscreen
Net weight	0,3 kg
Number of channels	4
OSD language	DE, GB, FR, NL, DK, IT
Plug type	DC-plug: 5,5 x 2,1 mm
Power consumption	8,4 W
Recording modes	Schedule, motion detection
Recording resolution @ frame rate per camera	3MP @15 fps
Resolution	1024 x 600p
Resolution modes	3 MP (2304 x 1296)
Screen diagonal	7 in
Sensitivity	-88 dBm
Storage medium	MicroSD Class 10 (max. 128GB)
Technology	Radio
Transmission channels	13
Transmission power	20 dBm
Video compression	H.264+
Views	1 / 4 (Quad)
Wireless range	(Depending on installation) 20 - 50 m
EAN	4043158205305

Technical data - ABUS EasyLook Camera

Base event	PIR & Software + Motion Mask
Channel width	20 MHz
Colour	Black
Compatible with	PPDF17000
Compatible with Secvest	No
Compatible with Smartvest	No
Compatible with wAppLoxx	No
DC voltage supply	12 V
Day/night switching	Auto
Dimensions	(W x L x H) 61 x 161 x 77 mm
Encryption	WPA2
Focal length	4 mm
Frequency range	2,403 - 2,478 GHz
Horizontal viewing angle	82 °
Housing material	Plastic

Technical data - ABUS EasyLook Camera

IP protection class	66
IR LEDs	Yes
IR range (up to)	15 m
IR swivel filter	Yes
Image sensor	1/3" CMOS
Loudspeaker	Yes
Max. humidity	90 %
Max. operating temperature	50 °C
Max. resolution @ frame rate	2305 x 1296 @15fps
Microphone	Yes
Min. humidity	30
Min. operating temperature	-10 °C
Minimum illumination (IR)	0,1 lx
Minimum illumination (colour)	1 lx
Net weight	0,3 kg
Optical Wave Length	940 nm
PIR range	8 m
PIR viewing angle	85 °
Plug type	DC-plug: 5,5 x 2,1 mm
Power consumption	3,6 W
Private zones	4
Resolution modes	2305 x 1296 (3MP)
Sensitivity	-88 dBm
Transmission power	20 dBm
Vertical viewing angle	42 °
Video bit rate	2Mbps
Video compression	H.264+
White balance	Auto
Wireless range	(Depending on installation) 20 - 50 m
EAN	4043158222340