

Metal distributor empty housing for 8 distributor strips

Art.-Nr. AZVT10000 Seite 1 von 2



DISTRIBUTION BOX FOR WIRED ALARM SYSTEM

Recommended installation accessories

With this universal distributor made of sturdy metal, you ensure clear wiring for your intruder alarm system. Especially when installing multiple control panels and detectors, it is recommended to install a distribution box at the nodes of your building.

Simple, flexible wiring

The empty housing accommodates up to 80 double connections (40 connections in 4CC). The distributor can be equipped with up to 8 PCB strips (10 wire pairs each), with optional LSA technology or LSA-Plus quick connection technology, solder or screw terminal strips.

Certified and secure

The distributor is protected against tampering with two cover contacts and is certified according to VdS class C. The housing is suitable for surface mounting indoors.

Technologies

- Main distribution box for wired alarm system
- Empty housing for up to 40 connections (4 CC) or 80 wire pairs
- For the installation of 8 PCB strips: LSA, solder and screw terminal strips with 10 wire pairs each (accessories required)
- Suitable for LSA-Plus quick connection system
- Possible wiring types: 2-wire, NO, NC, FSL
- Housing made of robust sheet steel, tamper monitoring; colour: pure white
- For surface mounting indoors



Metal distributor empty housing for 8 distributor strips

Art.-Nr. AZVT10000 Seite 2 von 2

Technical data - Metal distributor empty housing for 8 distributor strips

| Certifications | VdS C |
|----------------------------|--------------------|
| Dimensions | 280 x 199 x 43 mm |
| Environmental class | II |
| Gross weight | 1,625 kg |
| Height | 280 mm |
| Housing material | Sheet steel 1.5 mm |
| Installation location | Wall |
| Length | 43 mm |
| Max. humidity | 93 % |
| Max. operating temperature | 55 °C |
| Min. operating temperature | -25 °C |
| Net weight | 1,5 kg |
| PSTI conformity required | No |
| Sabotage monitoring | Yes |
| VdS approval no. | G 199045 |
| VdS class | С |
| Width | 199 mm |