

Keypad Terxon SX - 2023

Art.-Nr. AZBE10000

Seite 1 von 2



The LCD control panel is an extension module for the Terxon SX. Mounted near the entrance, it allows you to operate your alarm control panel quickly. The LCD control panel is connected to the Terxon SX via 4-wire bus wiring. Up to 4 control panels can be integrated into the alarm system. Installed in different parts of your building, these extension modules provide additional convenience. The system can be conveniently activated or deactivated from each control panel using a PIN code. The status of the alarm panel is also shown on the control panel's plain text display. System settings, programming and the 350-fold event memory of the Terxon SX can be viewed - and of course changed - at your leisure. The LCD control panel is an elegant white colour.

Technologies

- For operating and programming the Terxon SX alarm control panel
- For convenient arming/disarming of the alarm panel using a PIN code when leaving/entering the building
- Operating the alarm panel with PIN code and four-way navigation button
- Coloured LEDs to display the current system status

Technical data - Keypad Terxon SX - 2023

Certifications	without
Colour	weiß
Connections	RS485 BUS, Screw terminal für additional tamper contact
DC voltage supply	12 V
Dimensions	(WxHxD) 128x128x29 mm
Environmental class	II
Housing	ABS
Installation location	surface mount
Integrated siren	Yes
Length	29 mm

Keypad Terxon SX - 2023



Art.-Nr. AZBE10000

Seite 2 von 2

Technical data - Keypad Terxon SX - 2023

Max. humidity	93 %
Max. operating temperature	55 °C
Min. operating temperature	-10 °C
Net weight	0,2 kg
Power consumption	58 mA
Sabotage monitoring	Yes
Switching outputs	No
Width	128 mm