

# Base station ABUS Battery Cam Pro

Art.-Nr. PPIC91000X

Seite 1 von 1

## Technical data - Base station ABUS Battery Cam Pro

|                              |  |
|------------------------------|--|
| Alarming                     | Push notification / E-Mail                           |
| Audio compression            | PCM  |
| Audio output                 | Built-in Speaker                                     |
| Base event                   | PIR person detection / PIR motion detection / Manual |
| Colour                       | white  |
| Compatible with Secoris      | No   |
| Compatible with Secvest      | No   |
| Compatible with Smartvest    | Yes  |
| Compatible with wAppLoxx     | No   |
| DC voltage supply            | 12 V   |
| Dimensions                   | 150 x 110 x 25 mm                                    |
| Encryption                   | AES 128bit, WPA/WPA2-PSK                             |
| Frame rate                   | 15   |
| Frequency range              | 2,4 GHz  |
| Housing material             | plastic  |
| Loudspeaker                  | 85dB @ 10cm  |
| Max. humidity                | 90 %   |
| Max. operating temperature   | 40 °C  |
| Max. resolution @ frame rate | 3 MP @ 15 fps  |
| Min. humidity                | 0,1  |
| Min. operating temperature   | -10 °C   |
| Number of channels           | 4  |
| Number of users              | 3  |
| Power consumption            | 180 mA   |
| Private zones                | 3  |
| Recording modes              | max. 3 MP  |
| Resolution modes             | VGA / 720p / 1080p / 3 MP                            |
| Storage medium               | USB flash drive (up to 128 GB)                       |
| Technology                   | Network  |
| Total video channels         | 4  |
| Video Content Analysis (VCA) | Person detection                                     |
| Video compression            | H.264  |
| Video output                 | VGA / 720p / 1080p / 3 MP                            |