

# Tresorflex 1355/85 + bracket KF

Seite 1 von 2



## STRAIGHTFORWARD CONNECTING

A securely-chained bicycle doesn't always require a key. The ABUS Steel-O-Flex™ Tresorflex 1355 protects your bicycle with a personal numerical code.

And once you have adjusted the number reel after closing the lock, the sleeve-covered steel cable of the Steel-O-Flex™ Tresorflex 1355 effectively protects your bicycle from theft. The touch-protected number wheels prevent the mechanism from being tampered with by unauthorised persons. The wheels are designed in such a way that you can set your individual sequence for unlocking even in the dark. Simply open the lock, swing into the saddle and pedal - all without a key.

## Technologies

- 15 mm thick, overlapping steel shells protect the internal steel cable
- Plastic coating to prevent damage to the bicycle's paintwork
- Two-component number reel guarantees life-long visibility of the digits
- Special touch protection for increased security against unauthorised access to the code through manipulation of the mechanism
- Dark-touch function facilitates use in the dark thanks to special imprinting
- Individually configurable code

## Operation and use

- Good protection at low theft risk
- Recommended for protecting entry-level and children's bicycles

# Tresorflex 1355/85 + bracket KF

Seite 2 von 2

## Tips

- Due to the steel shells, the Steel-O-Flex™ locks reach a significantly higher security than common cable locks, yet maintaining high flexibility (Double Protection)
- The combination lock is great for use by several people

## Technical data - Tresorflex 1355/85 + bracket KF

|                 |                    |
|-----------------|--------------------|
| Length          | 85 cm              |
| Locking type    | number combination |
| Weight          | 618 g              |
| alarm function  | No                 |
| color of facets | black              |
| design color    | black              |
| diameter        | 15 mm              |
| EAN             | 4003318286827      |