4-Port PoE Gigabit Switch

Art.-Nr. ITAC10101

Technical data - 4-Port PoE Gigabit Switch

AC power supply	100 - 240 V
Application purpose	General surveillance
Connections	3 x Gigabit PoE Port, 1 x Gigabit Hi-PoE Port, 1 x Gigabit RJ45 Port
DC power supply	48 V
Depth	88 mm
Dimensions	121 x 88 x 27,5 mm
Gross weight	0.825 kg
Height	27.5 mm
Housing material	Metal
Language Manual	DE, GB, FR, NL, DK, IT
Language Packaging	DE, GB, FR, NL, DK, IT
Length	88 mm
Max. Air humidity	95 %
Max. Operating temperature	40 °C
Max. PoE power per port	4 x 15 watts or 2 x 30 watts or 1 x 60 watts (for max. power each port)
Min. operating temperature	0 °C
Net weight	0.255 kg
Network connection	Downstream: 4x 10/100/1000Base-T (PoE), Uplink: 1x 10/100/1000Base-T
Network standards	IEEE 802.3 af/at/bt, IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3x
Other functions	Port Isolation, PoE Watchdog, 6 KV Surge Protection, Fanless, Port 3 and 4 up to 300 m in extended mode
PSTI conformity given	No
PSTI conformity needed	No
Pin assignment Power supply	1/2(-), 3/6(+), 4/5(+), 7/8(-)
PoE Standard	IEEE 802.3 af/at/bt
Power consumption	65 W
Product group	Accessories
Total PoE power	60 W
WEEE group	09
width	121 mm

Subject to technical modifications. We assume no liability for mistakes and printing errors. © ABUS 10/2026