

Analogue Mini Tube 2 MPx (1080p, 2.8 mm)

Art.-Nr. HDCC32512

Seite 1 von 3



Analogue Mini Tube 2 MPx - detailed surveillance with existing technology

The Analogue Mini Tube with 2 megapixels is suitable for indoor and outdoor use (IP67) and delivers clear, detailed images - even in difficult lighting conditions. The True WDR function ensures balanced brightness between the foreground and background, while Gecko + IR technology enables colour images even at night. The camera is ideal for users who want to continue using existing coaxial cabling and at the same time benefit from modern image quality.

Targeted detection of people and vehicles

When used with an ABUS Analogue HDCC900X2 recorder, the camera enables AI-supported analysis. It distinguishes between people and vehicles, which improves the detection of relevant movements and reduces the number of irrelevant notifications.

Efficient retrofitting with existing infrastructure

Analogue technology makes it possible to modernise existing surveillance systems without replacing the existing coaxial or 2-wire cabling (via converters). Cameras and recorders can be easily replaced, which reduces time and installation effort. For reliable IR performance, the ambient conditions should be taken into account accordingly.

IR range depends on the environment

The performance of the lighting depends greatly on the location. Dark surfaces or a lack of reflections can have a negative effect on the image - as can close, reflective objects.

Technologies

- 2 MPx resolution: 1920 x 1080 @ 25 fps
- True WDR effectively equalises light/dark contrasts
- Fixed lens with 2.8 mm focal length and 105° horizontal viewing angle

Analogue Mini Tube 2 MPx (1080p, 2.8 mm)

Art.-Nr. HDCC32512

Seite 2 von 3

- Weatherproof (IP67) for outdoor use
- Integrated infrared LEDs with manual switching between IR and colour night vision
- Fewer false alarms thanks to AI-supported detection of people/vehicles with HDCC900X3 recorder
- Perfect for retrofitting: Transmission via conventional and existing CCTV infrastructure with coaxial cable
- Cable lengths of up to 250 m
- Wide variety of holders for straightforward, cost-efficient installation

Technical data - Analogue Mini Tube 2 MPx (1080p, 2.8 mm)

Aperture at minimum illumination (colour)	F1.0
Audio	Integrated: Microphone, Loudspeaker
Backlight compensation	WDR, HLC, HLS
Camera outputs	1 x BNC
Colour	white
Compatible with ABUS Link Station	No
Compatible with Comfion	No
Compatible with Secoris	No
Compatible with Secvest	No
Compatible with Smartvest	No
Compatible with wAppLoxx	No
Compatible with wAppLoxx Pro	No
Connections	1 x BNC (video), 1 x DC (5.5/2.1 mm)
DC voltage supply	12 (+/-25 %) V
Day/night switching	Electromechanical IR cut filter
Design	Mini tube
Dimensions	(LxWxH) 172x69x69 mm
Dynamic range (WDR)	130 dB
Electronic shutter	Auto (1/25 - 1/50000 s)
Focal length	2,8 mm
Functions	Motion Detection, Tripwire Detection and Intrusion Detection via DVR
Gross weight	0,51 kg
HD-TVI video channels	1
Height	69 mm
Horizontal viewing angle	105 °
Housing material	metal
IP protection class	67
IR LEDs	Yes

Analogue Mini Tube 2 MPx (1080p, 2.8 mm)

Art.-Nr. HDCC32512

Seite 3 von 3

Technical data - Analogue Mini Tube 2 MPx (1080p, 2.8 mm)

IR range (up to)	30 m
Image enhancement	WDR, BLC, HLC, HLS, ATW, 3D DNR
Image sensor	1/2.8" Progressive Scan CMOS
Language of instructions	DE, UK, FR, NL, DK, IT
Language packing	DE, UK, FR, NL, DK, IT
Length	172 mm
Lens	Fix
Max. humidity	90 %
Max. operating temperature	60 °C
Max. resolution @ frame rate	1920x1080 @ 25 frames/s
Microphone	Yes
Min. operating temperature	-30 °C
Minimum illumination (IR)	0 lx
Minimum illumination (colour)	0,0005 lx
Net weight	0,452 kg
Noise reduction	3D DNR
OSD language	UK
Other functions	White light up to 20 meters
PSTI conformity required	No
Pixels (effective)	1920 x 1080 pixel
Power consumption	750 mA
Private zones	using ABUS DVR
Protocols	No
Resolution	2 MP
Resolution modes	1920 x 1080
Technology	Analogue HD
Vertical viewing angle	56 °
Video system	HD-TVI
White balance	ATW, manual
Width	69 mm