

# 10.4" LED monitor with BNC input

Art.-Nr. TVAC10002

Seite 1 von 2



## COMPACT LED MONITOR

The versatile monitor for countless applications in video surveillance and industry. The compact size of 10.4" is ideal for use or installation in checkout areas or other confined spaces. With its analogue BNC input and output, the monitor can also be used as a spot monitor for live surveillance or as a confrontation monitor in retail.

The monitor has a resolution of 800 x 600 pixels and displays images in 4:3 format. It delivers brilliant images with high contrasts. Thanks to the LED backlighting, details and colours are displayed particularly precisely and true to life. For informative scenes, for example in the live view or playback.

Easy to connect and flexible to use: with its numerous connections (HDMI, VGA, BNC input, BNC output, audio input), the monitor can be easily and quickly connected to various devices and systems, e.g. security cameras with BNC output, surveillance recorders or PC. In addition, the monitor is compatible with commercially available VESA brackets and can thus be easily mounted on walls. This saves space at the workstation (desk, counter, gate) and makes it easy to mount the unit as a spot or confrontation monitor, e.g. on the sales floor. It delivers good sound quality via the integrated loudspeaker and can also output sound recordings from cameras with 2-way communication.

## Technologies

- High contrast 10.4 LED monitor (4:3 format)
- Resolution: 800 x 600 pixels
- Connections: 1 x HDMI, 1 x VGA, 1 x BNC input, 1 x BNC output, 1 x audio input
- LED backlighting: Brilliant colour display and high contrast
- Integrated loudspeaker
- Compatible with VESA brackets
- Compact dimensions: ideal for checkout areas, for example

# 10.4" LED monitor with BNC input

Art.-Nr. TVAC10002

Seite 2 von 2

## Technical data - 10.4" LED monitor with BNC input

|                                      |   |
|--------------------------------------|---|
| Application purpose                  | General surveillance                                  |
| Brightness                           | 300   |
| Color levels                         | 16.7  |
| Colour                               | black   |
| Comb filter                          | 3D  |
| Connection type                      | 1 x HDMI, 1 x VGA, 1 x BNC in, 1 x BNC out, 1 x Audio |
| Current consumption                  | 1,500 mA  |
| DC power supply                      | 12 V  |
| Dimensions                           | (W x H x D) 268 x 222 x 29 mm                         |
| Display surface                      | mat   |
| Frequency range                      | 31.5 - 80 kHz (H) / 56 - 75 Hz (V) GHz                |
| Height                               | 222 mm  |
| Housing material                     | Plastic   |
| Image format                         | 4:3   |
| Length                               | 29 mm   |
| Loudspeaker                          | Integrated 2 x 2.5 W Stereo                           |
| Max. Air humidity                    | 70 %  |
| Max. Operating temperature           | 40 °C   |
| Max. number of video feeds           | 3   |
| Min. operating temperature           | -10 °C  |
| Monitor type                         | Standard TFT LCD                                      |
| Net weight                           | 1.55 kg   |
| Power consumption                    | 11.5 W  |
| Product group                        | Accessories   |
| Response time                        | 8 ms  |
| Screen diagonal                      | 10.4 in   |
| Signal detection                     | Automatic   |
| Video system                         | PAL / NTSC  |
| Viewing angle<br>horizontal/vertical | 150°/110°   |
| WEEE group                           | 09  |
| width                                | 268 mm  |