

ABUS Transponder Advanced white MIFARE DESFire EV3 8K (Security)

Art.-Nr. ACTP00008W

Seite 1 von 2



THE DIGITAL KEY FOR ELECTRONIC LOCKING SYSTEMS & EMA SYSTEMS.

Contactless locking medium

The battery-free RFID key fob is the locking medium for ABUS access control systems and other ABUS security systems with MIFARE® DESFire® technology.

Universally applicable

The RFID transponder can be used as a locking medium for wAppLoxx Pro, wAppLoxx Pro Plus and TECTIQ systems. (Please note: wAppLoxx Cylinders of Generation 1 do not work with MIFARE® DESFire® EV3). It also allows you to operate ABUS security systems, such as the Secoris intruder alarm system. Thanks to its robust design, the key fob is suitable for indoor and outdoor use (IP64). As a passive transponder, it does not require a battery.

Secure ease of use

Thanks to 13.56 MHz RFID technology, these ABUS systems can be operated conveniently, securely readout-protected and contactless. The pre-programmed ABUS "security application" also guarantees maximum protection against copying and tampering based on MIFARE® DESFire® EV3 8K technology.

Desired colour variant?

The key fob is available in green, blue, red, black or white.

Technologies

- Attractive RFID key fob with stainless steel mounting bracket (MIFARE® DESFire® EV3 8K)
- Contactless opening of all ABUS WLX Pro and TECTIQ door components (cylinders, fittings, wall readers, etc.)
- Operation of other ABUS security systems, e.g. Secoris burglar alarm system
- Maximum copy and tamper protection with pre-programmed ABUS security application

ABUS Transponder Advanced white MIFARE DESFire EV3 8K (Security)

Art.-Nr. ACTP00008W

Seite 2 von 2

- Robust design for long-lasting use on key rings (resists dust, dirt and moisture)
- Simple assignment of transponder to persons thanks to serial number on the back
- Passive transponder without battery

Technical data - ABUS Transponder Advanced white MIFARE DESFire EV3 8K (Security)

Area of application	Locking medium for ABUS access control systems (WLX Pro & TECTIQ)
Colour	white
Design	Keyfob
Dimensions	36,5 x 45,3 x 5,5 mm
IP protection class	64
Item abbreviation	T-MIF-DES-ADV-8K-SEC-W
Material	Novodur (body), polished stainless steel (frame)
Max. operating temperature	50 °C
Min. operating temperature	-20 °C
Programming technology	RFID (13,56 MHz)
RFID conformity	ISO 14443
RFID frequency	13,56 MHz
RFID technology	MIFARE® DESFire® EV3
Reader type	MIFARE® DESFire® 8K EV3 (70pf)
Security features	Copy and read protection with MIFARE® DESFire® + ABUS security application and Random ID
Transponder conformity	Passive transponder ISO 14443 A (MIFARE® DESFire®)
Transponder encryption	AES 128-Bit
Transponder programming	Access control software and card reader