

# 24" Full HD LED Monitor

Art.-Nr. TVAC10062

Seite 1 von 2

## Detailed surveillance images in Full HD

The convenient LED monitor with a 24 (inch) screen diagonal displays detailed surveillance images in 16:9 format and Full HD 1080p resolution.

## Full HD monitor for easy identification

Thanks to its fast response time (only 5 ms), the LED monitor displays surveillance images with virtually no delay. It displays fast movements on the screen clearly and smoothly - without distortion, flickering or ghosting. You see detailed images in Full HD quality, allowing you to observe, easily identify people and quickly clarify situations. Connections for versatile use Flexibly connect the monitor to a recorder or PC. Thanks to the HDMI input, the screen is ideal for displaying Full HD images. An additional VGA input ensures connection to a wide range of surveillance systems, computers and other components.

## Energy efficiency for continuous monitoring

The efficient LED display ensures low power consumption - ideal for continuous use.

## Easy installation with VESA mounts

The monitor is compatible with standard VESA mounts for quick installation on a wall or ceiling.

Tip: The monitor is also available in 27 with 4K resolution (TVAC10071).

## Technologies

- 24 LED monitor with full HD resolution: 1920 x 1080 pixels
- Fast reaction time (5 ms) for flowing images
- Brilliant colour display and high contrast in 16:9 format
- Ideal for high-resolution full HD recording systems
- Graphical on-screen display (OSD)
- Connections: HDMI, VGA
- Low power consumption for long-term monitoring (LED technology)
- Compatible with VESA brackets for wall and ceiling installation

## Technical data - 24" Full HD LED Monitor

Application purpose	General surveillance
Brightness	250
Color levels	16.7
Colour	black
Connections	1 x HDMI (1.4), 1 x VGA, 1 x DC, 1 x Audio-out

# 24" Full HD LED Monitor



Security Tech Germany

Art.-Nr. TVAC10062

Seite 2 von 2

## Technical data - 24" Full HD LED Monitor

Contrast ratio	4000:1
Current consumption	2,000 mA
DC power supply	12 V
Depth	165 mm
Dimensions	540 x 400 x 165 mm
Display surface	matt
Gross weight	3.85 kg
Height	400 mm
Housing material	Plastic
Image format	16:9
Input	1 x HDMI (1.4), 1 x VGA
Length	165 mm
Max. Air humidity	90 %
Max. Operating temperature	40 °C
Max. number of video feeds	2
Min. operating temperature	0 °C
Monitor type	LED
Net weight	2.85 kg
Power consumption	24 W
Product group	Accessories
Response time	7 ms
Screen diagonal	23.8 in
Video output	1 x Audio (3.5 mm phone jack)
Viewing angle horizontal/vertical	178° x 178°
WEEE group	09
width	540 mm