

## KKZS700 for flat entrance doors in F2: Anodized silver (Handle plate/Door handle)

Seite 1 von 2



### THE FLAT SECURED

Protect your front door with this door fitting made of high-quality steel.

Burglars usually only have to make a few moves to gain access to your home. The reason: Door cylinders that stick out far. These can be pulled out. Make your flat door more secure with this door fitting in a compact design. The compact door hardware is particularly characterised by its high resistance to pulling attempts. In addition, extra-long steel cams and hardened and tempered special screws as well as the structure made of different steel layers increase your safety. The door hardware is suitable for flat doors with a door thickness of 37 to 47 millimetres. It is VdS and DIN certified.

### **Technologies**

- Certified according to DIN EN 1906 SK 2 and DIN 18 257 ES 1 ZA, VdS approved
- Short cover plate
- Maximum resistance due to the layer construction: several bottom plates for maximum protection
- · High impact resistance: extra long steel cams, complete with tempered special screws
- An additional steel inset provides extra strong leverage/tear-off resistance
- Integrated pulling protection with cylinder cover plus freely rotating special steel disc
- Grip plate adjustable to DIN left and right doors
- · Spacing: 72 mm, square bolt: 8 mm

### Operation and use

For apartment doors



# KKZS700 for flat entrance doors in F2: Anodized silver (Handle plate/Door handle)

Seite 2 von 2

- · Suitable for rebated and flush doors, left and right opening
- Grip plate outside, handle inside
- Suitable for door thicknesses of 37 47 mm
- Mounting material for deviating door thicknesses can be supplied

#### Variants

- Finishes: F1 (alu anodized), F2 (silver anodized), F3 (anodized brass), F4 (anodized bronze)
- Alternatively available as a handle/handle set
- Model fire protection (only in F1)

## Technical data - KKZS700 for flat entrance doors in F2: Anodized silver (Handle plate/Door handle)

Beidseitig Drücker	No
Cylinder protrusion	10-18 mm
Distance measure	72 mm
Door fitting for fire doors	No
Door type	Apartment door
Interchangeable fitting	Yes
Security Level Home Security	8
Weight	905 g
colour	F2: Aluminum Nickel Silver
pulling protection	Yes
EAN	4003318089633

## Technical drawing





