

KKT512 for flat entrance doors in F1: Aluminum (Handle plate/Door handle)

Seite 1 von 2



UNIVERSAL AND SAFE

Protect your flat door against burglars with this door fitting.

On flat doors, the door cylinder often protrudes slightly. A weak point that burglars exploit to break into homes without permission. Your flat door can also fall victim to this method. Unless you secure them with a reliable door fitting. This compact door hardware is suitable for universal use on flat doors with a door thickness of 37 to 47 millimetres, regardless of whether they are right-hand or left-hand closing. The layered construction of several steel plates makes it particularly safe. A steel insert in the handle provides high tear-off protection. Hardened and tempered special screws and extra-long steel cams secure against violent break-off attempts.

Technologies

- Certified according to DIN EN 1906 SK 2 and DIN 18 257 ES, VdS approved
- Short cover plate
- Maximum resistance due to the layer construction: several bottom plates for maximum protection
- High impact resistance: extra long steel cams, complete with tempered special screws
- An additional steel inset provides extra strong leverage/tear-off resistance
- Grip plate adjustable to DIN left and right doors
- Spacing: 72 mm, square bolt: 8 mm

Operation and use

- For apartment doors
- Suitable for rebated and flush doors, left and right opening

KKT512 for flat entrance doors in F1: Aluminum (Handle plate/Door handle)

Seite 2 von 2

- Grip plate outside, handle inside
- Suitable for door thicknesses of 37 - 47 mm
- Mounting material for deviating door thicknesses can be supplied

Variants

- Finishes: F1 (alu anodized), F2 (silver anodized)
- Alternatively available as a handle/handle set

Technical data - KKT512 for flat entrance doors in F1: Aluminum (Handle plate/Door handle)

Beidseitig Drücker	No
Cylinder protrusion	12 mm
Distance measure	72 mm
Door fitting for fire doors	No
Door type	Apartment door
Interchangeable fitting	Yes
Security Level Home Security	6
Weight	865 g
colour	F1: Aluminum Nature
pulling protection	No
EAN	4003318264399

Technical drawing

