



#### LIGHTWEIGHT BUT SAFE

Secure items at average risk of theft with our 64 TITANIUM™ padlock.

Whether doors or gates, cupboards or lockers, toolboxes or cellars: With this padlock your valuables are very well protected against theft. The lock body is made of TITANIUM™ special aluminium, which makes it particularly lightweight, yet robust. The paracentric key profile provides increased protection against manipulation, making attempts to break open the padlock 64 Titanium more difficult. If you need to connect locking points that are further apart, choose a version with a high bracket. This allows you to lock even thicker chains or solid locking bolts easily and comfortably.

#### Technologies

- Solid lock body made from TITANIUM™ special aluminium
- Hardened steel shackle with NANO PROTECT™ coating for extreme corrosion resistance
- 64TI/50HB60-150: Removable and adjustable shackle from 60 mm to 150 mm
- Paracentric key profile for increased protection against manipulation
- Double bolted shackle
- Chrome-plated cylinder plug for additional corrosion protection
- Tulip-shaped key head

#### Operation and use

- Security for items/goods of medium value or where there is an average risk of theft
- For securing e.g. chains, doors, gates, cupboards, lockers, tool boxes, cellar windows or sheds

**Technical data - 64TI/35**

|                              |               |
|------------------------------|---------------|
| Depth e                      | 14 mm         |
| Height f                     | 54 mm         |
| Horizontal clearance b       | 19 mm         |
| Keyed alike                  | No            |
| Locking type                 | key           |
| Security Level Home Security | 4             |
| Security card                | No            |
| Shackle diameter d           | 5,5 mm        |
| Vertical clearance c         | 20 mm         |
| Weight                       | 69 g          |
| Width a                      | 35 mm         |
| colour                       | aluminum      |
| EAN                          | 4003318561948 |

**Technical drawing**