

# KLS114 ZS for flat entrance doors in F1: Aluminum (Handle plate/Door handle)

Seite 1 von 2



## THE FLAT SECURELY LOCKED

Universal door fitting for flat doors with integrated cylinder, pull and tear-off protection.

A flat door must do one thing above all: close securely. However, many are inadequately secured. The reason: Burglars can take advantage of the fact that the lock cylinder of a door often sticks out a little. They can remove it by force and thus gain access to your home. Therefore, secure your home with a reliable door fitting. The door hardware is especially suitable for flat front doors and is characterised in particular by the protection of the locking cylinder against being pulled out. Multi-layer steel makes the door hardware particularly robust. It is suitable for mounting on flat doors with a door thickness of 37 to 47 millimetres.

## Technologies

- According to DIN EN 1906 SK 1 and DIN 18 257 ES 0
- Integrated pulling protection with cylinder cover plus freely rotating special steel disc
- Increased leverage resistance: solid cams plus inner screws
- Proven layered construction: hardened steel bottom plate, plus sturdy cover plate
- Spacing: 72 mm, square bolt: 8 mm
- Just one version is necessary to cover cylinder protrusions from 10 - 18 mm

## Operation and use

- For apartment doors
- Grip plate outside, handle inside
- Suitable for door thicknesses of 37 - 47 mm

# KLS114 ZS for flat entrance doors in F1: Aluminum (Handle plate/Door handle)

Seite 2 von 2

- Mounting material for deviating door thicknesses can be supplied

## Variants

- Finishes: F1 (alu anodized), F2 (silver anodized)
- Alternatively available as a handle/handle set

## Technical data - KLS114 ZS for flat entrance doors in F1: Aluminum (Handle plate/Door handle)

Beidseitig Drücker	No
Cylinder protrusion	10-18 mm
Distance measure	72 mm
Door fitting for fire doors	No
Door type	Apartment door
Interchangeable fitting	Yes
Security Level Home Security	6
Weight	920 g
colour	F1: Aluminum Nature
pulling protection	Yes
EAN	4003318211300

## Technical drawing

