

# KLS114 for flat entrance doors in F2: Anodized silver (Handle plate/Door handle)

Seite 1 von 2



## UNIVERSAL AND RELIABLE

Flat doors are often inadequately secured. A door fitting can change that.

You always want to be able to exit out of your front door. Whether you are at home or on the road. But often they are not sufficiently secured. Common problem: Lock cylinders protrude somewhat. Burglars can then simply remove them by force and enter your home. Make your flat door more secure with a door fitting. This door hardware is specially designed for universal use on flat doors with door thicknesses from 37 to 47 millimetres. It is composed of a metal lower shield and a lightweight metal upper shield. Internal bolting and strong cams increase breakaway protection.

## Technologies

- According to DIN EN 1906 SK 1 and DIN 18 257 ES 0
- Increased leverage resistance: solid cams plus inner screws
- Proven layered construction: hardened steel bottom plate, plus sturdy cover plate
- Thickness: 15 mm
- Spacing: 72 mm, square bolt: 8 mm

## Operation and use

- For apartment doors
- Grip plate outside, handle inside
- Suitable for door thicknesses of 37 - 47 mm
- Mounting material for deviating door thicknesses can be supplied

## Variants

# KLS114 for flat entrance doors in F2: Anodized silver (Handle plate/Door handle)

Seite 2 von 2

- Finishes: F1 (alu anodized), F2 (silver anodized), F3 (anodized brass), F4 (anodized bronze), F9 (stainless steel look)
- Alternatively available as a handle/handle set

## Technical data - KLS114 for flat entrance doors in F2: Anodized silver (Handle plate/Door handle)

Beidseitig Drücker	No
Cylinder protrusion	15 mm
Distance measure	72 mm
Door fitting for fire doors	No
Door type	Apartment door
Interchangeable fitting	Yes
Security Level Home Security	5
Weight	904 g
colour	F2: Aluminum Nickel Silver
pulling protection	No
EAN	4003318083006

## Technical drawing

