

KLN314 ZS F2 two handles

Seite 1 von 2



Technologies

- According to DIN EN 1906 SK 1 and DIN 18 257 ES 0
- Integrated pulling protection with cylinder cover plus freely rotating special steel disc
- Increased leverage resistance: solid cams plus inner screws
- Proven layered construction: hardened steel bottom plate, plus sturdy cover plate
- Spacing: 72 mm, square bolt: 8 mm

Operation and use

- For apartment doors
- Grip plate outside, handle inside
- Suitable for door thicknesses of 37 - 47 mm
- Mounting material for deviating door thicknesses can be supplied

Variants

- Finish: F2 (silver anodized)
- Alternatively available as a handle/handle set

Technical data - KLN314 ZS F2 two handles

| | |
|------------------------------|----------------|
| Beidseitig Drücker | Yes |
| Cylinder protrusion | 10 - 18 mm |
| Distance measure | 72 mm |
| Door fitting for fire doors | No |
| Door type | Apartment door |
| Interchangeable fitting | No |
| Security Level Home Security | 6 |

KLN314 ZS F2 two handles

Seite 2 von 2

Technical data - KLN314 ZS F2 two handles

| | |
|--------------------|----------------------------|
| Weight | 1125 g |
| colour | F2: Aluminum Nickel Silver |
| pulling protection | Yes |
| EAN | 4003318208942 |

Technical drawing

