



Technologies

- According to DIN EN 1906 SK 1 and DIN 18 257 ES 0
- Integrated pulling protection with cylinder cover plus freely rotating special steel disc
- Increased leverage resistance: solid cams plus inner screws
- Proven layered construction: hardened steel bottom plate, plus sturdy cover plate
- HLN ZS: Spacing: 92 mm, square bolt: 10 mm
- KLN ZS: Spacing: 72 mm, square bolt: 8 mm

Operation and use

- For main entrance doors (HLN) and apartment doors (KLN)
- Grip plate outside, handle inside
- HLN: Suitable for door thicknesses of 52 - 67 mm
- KLN: Suitable for door thicknesses of 37 - 47 mm
- Mounting material for deviating door thicknesses can be supplied

Variants

- Finish: F2 (silver anodized)
- Alternatively available as a handle/handle set

Technical data - HLN414 ZS F2 CL/DFNLI

Beidseitig Drücker	No
Cylinder protrusion	10 - 18 mm
Distance measure	92 mm
Door fitting for fire doors	No
Door type	Entry door

HLN414 ZS F2 CL/DFNLI

Technical data - HLN414 ZS F2 CL/DFNLI

Interchangeable fitting	Yes
Security Level Home Security	6
Weight	1240 g
colour	F2: Aluminum Nickel Silver
pulling protection	Yes
EAN	4003318203695

Technical drawing

