



TRUST THE ORIGINAL

Our padlock Diskus® 24IBWY is weatherproof and has proven itself to secure high value assets or objects with a high risk of theft.

The round shape with narrow stirrup opening and the welding seam ensure solid safety! The padlock Diskus® 24IBWY protects your valuables especially in sea and harbour areas or if you want to secure boxes, crates and more on boats or on vehicles in outdoor use (pickup trucks, trucks and the like). Lock body and shackle are made of stainless steel, which makes it particularly weather-resistant. The seam that holds the two stainless steel shells together is welded by hand. This means that the two halves cannot simply be broken apart. Tip: Combine the Diskus® 24IBWY with the matching hasp 140. A safety plus: In the WY version you receive the Diskus® 24IBWY with security card. This way you keep control: Original keys can only be duplicated on presentation of the enclosed security card at a licensed ABUS specialist dealer.

Technologies

- Body, inner parts and shackle made from stainless steel for extreme corrosion resistance
- Cylinder cover - maximum protection against dirt and moisture (60 and 70 mm)
- Cylinder nickel plated for enhanced corrosion resistance
- Original Diskus design: 360° protection
- Diskus Deep-Welding Technology - maximum strength
- Precision pin tumbler cylinder with anti-pick pins
- Key retaining: locking only with the key (lock retains key until locked)
- Made in Germany

- WY: comes with security card to protect against unauthorized key duplicates

Operation and use

- To secure valuables / goods of greater value or at a high risk of theft
- Ideal for use in severe weather conditions (e.g. in coastal regions or ports)
- To secure lorries, doors, gates, cellar doors, cupboards etc.
- Ideally used with ABUS Diskus Hasp 140: virtually impossible to attack shackle

Technical data - Diskus® 24WYIB/70

Depth e	29 mm
Height f	70 mm
Horizontal clearance b	20 mm
Keyed alike	No
Locking type	key
Security Level Home Security	6
Security card	Yes
Shackle diameter d	10 mm
Vertical clearance c	17 mm
Weight	325 g
Width a	70 mm
colour	stainless steel
EAN	4003318823305

Technical drawing

