

# Half cylinder A93

Seite 1 von 2



## Door Cylinder A93

Perfect for people who are looking for one or more reliable door cylinders that feature classic standard functions.

The Door Cylinder A93 is available in nearly all lengths up to a total length of 160mm and in half cylinder and knob cylinder variants. The A93 has an emergency function in lengths of 28/34 and above. The hardened components provide substantial protection against drilling. This means that the door cylinder cannot be drilled out and then removed in order to open the door.

## Technologies

- DIN EN 1303 (160B0C6A/C \* ) and DIN18252 (M04A/C \* 0/FZG) tested; ISO 9001:2015
- \* Class C only in combination with a security plate class ES1-ZA acc. to DIN 18257 or class SK2 with ZA acc. to DIN EN 1906
- With emergency function: can be locked from both sides, even if the key is in the lock inside (does not apply to half cylinders, as these can only be locked from the outside)
- Free-turning function (suitable for FZG tested doors)
- Tested application in RC2 doors (in combination with a suitable door fitting)
- Anti-drill protection by hardened steel pins
- 5 pin cylinder
- 11mm long key neck (perfect for door fittings with pulling protection)
- Conversion set A93 for conversion to knob cylinder optionally available
- ABUS Global Protection Standard (GPS) 6
- with 3 coded keys

