

KFG square for fire doors (Door handle on both sides)

Seite 1 von 2



SURE THING

Poorly secured doors make it easy for burglars. This door fitting changes that.

If your door is unprofessionally secured, burglars will have an easy time. If you want to protect your entrances and exits against unauthorised entry, you need a robust door fitting made of high-quality materials. This product is made of steel and low-wear plastic. Thanks to pre-assembled steel cams, it is quickly mounted and can easily withstand a tensile load of 2.5 tonnes. It is specially designed for fire doors. The steel core inside ensures operation in an emergency. Alternatively, the door fitting is also available as a handle/handle set.

Technologies

- According to DIN 18 273, supervised by the MPA (German institute for testing of materials)
- Steel base plate plus cover made from high quality PVC
- Steel core in PVC handle
- Easy to fit with pre-fixed steel cams
- Spacing: 72 mm, square bolt: 9 mm
- U-lever shape

Operation and use

- Door fitting for fire doors
- Grip plate outside, handle inside
- Suitable for door thicknesses of 40 - 66 mm

Variants

KFG square for fire doors (Door handle on both sides)

Seite 2 von 2

- Finish: black
- Alternatively available as a handle/handle set

Technical data - KFG square for fire doors (Door handle on both sides)

Beidseitig Drücker	Yes
Cylinder protrusion	9 mm
Distance measure	72 mm
Door fitting for fire doors	Yes
Door type	Fire door
Interchangeable fitting	No
Security Level Home Security	4
Weight	604 g
colour	black
pulling protection	No
EAN	4003318215230

Technical drawing

