

HLN414 F2 two handles CL/DFNLI

Seite 1 von 2



Technologies

- According to DIN EN 1906 SK 1 and DIN 18 257 ES 0
- Increased leverage resistance: solid cams plus inner screws
- Proven layered construction: hardened steel bottom plate, plus sturdy cover plate
- Thickness: 15 mm
- Spacing: 92 mm, square bolt: 10 mm

Operation and use

- For main entrance doors
- Grip plate outside, handle inside
- Suitable for door thicknesses of 52 - 67 mm
- Mounting material for deviating door thicknesses can be supplied

Variants

- Finishes: F1 (alu anodized), F2 (silver anodized), F3 (anodized brass), F4 (anodized bronze), F9 (stainless steel look), white
- Alternatively available as a handle/handle set
- Also available with cylinder protection (ZS)

Technical data - HLN414 F2 two handles CL/DFNLI

Beidseitig Drücker	Yes
Cylinder protrusion	15 mm
Distance measure	92 mm
Door fitting for fire doors	No
Door type	Entry door

HLN414 F2 two handles CL/DFNLI

Technical data - HLN414 F2 two handles CL/DFNLI

Interchangeable fitting	No
Security Level Home Security	5
Weight	1043 g
colour	F2: Aluminum Nickel Silver
pulling protection	No
EAN	4003318091810

Technical drawing

