

# SKG-IKOB PRODUCTCERTIFICATE

## 466.313.10

Date of issue: 17-05-2021



### Certificate holder

ABUS Pfaffenhain GmbH  
Fabrikstraße 1  
D-09387 Jahnsdorf  
T: +49 (0) 37296 7130  
E: info@abus-pfaffenhain.de  
I: www.abus-pfaffenhain.de



### Declaration of SKG-IKOB

This certificate has been issued on the basis of BRL 3104 in accordance with the SKG-IKOB Regulations for Attestation, Certification and Inspection.

SKG-IKOB declares that the by or on behalf of the certificate owner produced building hardware product:

### euro profile cylinder with non lockable knob

delivered under logo / brand:

### PFAFFENHAIN / ABUS

delivered under type- and / or article number:

**B1L430 SKG3 , B2L430 SKG3 , B3L430 SKG3**  
**VE1L491-30\_SKG3 , VE2L491-30\_SKG3**  
**VE1L430 SKG3 , VE2L430 SKG3**

meets class 3 STER according BRL 3104 and NEN 5089: 2009 if the product is indelibly marked with the SKG mark, as shown above.

For SKG-IKOB

A handwritten signature in blue ink, consisting of a stylized, cursive script that appears to be "H.A.J. van Dartel".

ir. H.A.J. van Dartel  
Certification manager

Verify at [www.sterrenwijzer.nl](http://www.sterrenwijzer.nl) if this certificate is still valid and actual.  
This certificate contains 2 pages.

SKG-IKOB Certificatie  
Poppenbouwing 56  
4191 NZ Geldermalsen

Postbus 202  
4190 CE Geldermalsen

T 088-2440100  
info@skgikob.nl  
www.skgikob.nl

CERTIFICATE

# SKG-IKOB PRODUCTCERTIFICATE

ABUS Pfaffenhain GmbH  
Number: 466.313.10

page 2 of 2

## 1. PRODUCT

euro profile cylinder with non lockable knob

## PRODUCT TYPE

cylinder

---

## 2. TECHNICAL SPECIFICATION

Operating:	Mechanical operation
Construction:	double, with push-knob OR standard knob with OR without fracture line
System:	horizontal key profile 1 row of 6 mechanical operated retainers + 2 rows of resp. 6/5 block elements with OR without activation pawl on the 2nd key option
Material:	cylinder body: brass with various coatings
Dimension:	17 mm profile from 30 mm in various extensions per 5 mm
Fixing:	1 steel bolt M5, length $\geq$ backset + 10 mm
Intended use:	in combination with cylinder mortice locks and security furniture. Pay Attention! This cylinder achieves only the SKG-star rating if a door element (including side window), wherein at least P4A glass has been applied, OR in a door element (including side window) with a section filling without a view on the knob. A wooden door element (including side window) with a view to the "standard" turning knob, should be provided with a SKG (V) certified anti-drill / manipulation device.

---

## 3. DELIVERY

The delivery includes an installation instruction:  
EK-DR-0051-06.2020  
VERPA015-042020

---

## 4. PERFORMANCES

A euro profile cylinder with non lockable knob according this certificate fulfils the relevant requirements of BRL 3104.

A window- or door set, in which this euro profile cylinder with non lockable knob is installed according the installation instructions of the certificate holder meets at least burglar resistance class (RC) 3 of NEN 5096 and EN 1627, if:

the façade element or the (profile-)system from which the element is manufactured is delivered under a (KOMO-)quality approval with respect to the aspect burglar resistance, in which the actual window or door type is admitted and the herein mentioned conditions are fulfilled.

A window or door, in existing buildings, in which this euro profile cylinder with non lockable knob is installed according the installation instructions of the certificate holder, meets the requirements of the Police Mark Save Housing (PKVW) - Existing Building, if:

the other aspects of the façade element also comply with the applicable PKVW Protection directive (publication CCV).

---

# SKG-IKOB PRODUCTCERTIFICATE

## 466.313.09

Date of issue: 17-05-2021



### Certificate holder

ABUS Pfaffenhain GmbH  
Fabrikstraße 1  
D-09387 Jahnsdorf  
T: +49 (0) 37296 7130  
E: info@abus-pfaffenhain.de  
I: www.abus-pfaffenhain.de



### Declaration of SKG-IKOB

This certificate has been issued on the basis of BRL 3104 in accordance with the SKG-IKOB Regulations for Attestation, Certification and Inspection.

SKG-IKOB declares that the by or on behalf of the certificate owner produced building hardware product:

### euro profile cylinder

delivered under logo / brand:

### PFAFFENHAIN / ABUS

delivered under type- and / or article number:

**B1L410 SKG3, B2L410 SKG3, B3L410 SKG3,  
B1L430-AK SKG3, B2L430-AK SKG3, B3L430-AK SKG3,  
B1L452 SKG3, B2L452 SKG3, B3L452 SKG3,  
VE1L410 SKG3, VE2L410 SKG3,  
VE1L430-AK SKG3, VE2L430-AK SKG3,  
VE1L452 SKG3, VE2L452 SKG3**

meets class 3 STER according BRL 3104 and NEN 5089: 2009 if the product is indelibly marked with the SKG mark, as shown above.

For SKG-IKOB

A handwritten signature in blue ink, appearing to be "H.A.J. van Dartel", written over a light blue background.

ir. H.A.J. van Dartel  
Certification manager

Verify at [www.sterrenwijzer.nl](http://www.sterrenwijzer.nl) if this certificate is still valid and actual.  
This certificate contains 2 pages.

SKG-IKOB Certificatie  
Poppenbouwing 56  
4191 NZ Geldermalsen

Postbus 202  
4190 CE Geldermalsen

T 088-2440100  
info@skgikob.nl  
www.skgikob.nl

CERTIFICATE

# SKG-IKOB PRODUCTCERTIFICATE

ABUS Pfaffenhain GmbH  
Number: 466.313.09

page 2 of 2

**1. PRODUCT**  
euro profile cylinder

**PRODUCT TYPE**  
cylinder

---

## 2. TECHNICAL SPECIFICATION

Operating:	Mechanical operation
Construction:	double OR single with various couplings STD: standard function GKUP: emergency and hazard function PKUP: freewheel function with or without lockable knob with OR without fracture line
System:	horizontal key profile 1 row of 6 mechanical operated detainers + 2 rows of resp. 6/5 block elements with OR without activation pawl on the 2nd key option
Material:	cylinder body: brass with various coatings
Dimension:	17 mm profile from 30 mm in various extensions per 5 mm
Fixing:	1 steel bolt M5, length $\geq$ backset + 10 mm
Intended use:	in combination with cylinder mortice locks and security furniture

---

## 3. DELIVERY

The delivery includes an installation instruction:  
EK-DR-0051-06.2020

---

## 4. PERFORMANCES

A euro profile cylinder according this certificate fulfils the relevant requirements of BRL 3104.

A window- or door set, in which this euro profile cylinder is installed according the installation instructions of the certificate holder meets at least burglar resistance class (RC) 3 of NEN 5096 and EN 1627, if:

the façade element or the (profile-)system from which the element is manufactured is delivered under a (KOMO-)quality approval with respect to the aspect burglar resistance, in which the actual window or door type is admitted and the herein mentioned conditions are fulfilled.

A window or door, in existing buildings, in which this euro profile cylinder is installed according the installation instructions of the certificate holder, meets the requirements of the Police Mark Save Housing (PKVW) - Existing Building, if:

the other aspects of the façade element also comply with the applicable PKVW Protection directive (publication CCV).

---