

Secvest 2WAY FOS 550 E wireless window bar lock, white

Art.-Nr. FU8421W

Seite 1 von 1

Technologies

- Suitable for windows and French doors with inward-opening turn and turn-tilt fittings
- With automatic locking (window closed = window secured)
- 2 locking points with a pressure resistance of over one tonne
- Active intrusion protection (detects even attempted break-ins)
- Required accessories: Locking bars (available in various lengths)
- Keyed alike: 1 key for all units, 3 bittings available

Technical data - Secvest 2WAY FOS 550 E wireless window bar lock, white

Battery - max. battery life	2 years(s)
Battery type	2 x 1.5 V LR03 AAA alkaline batteries
Certifications	VdS (mechanism)
Connections	Clamping terminal
DC power supply	3 V
Detection method	Magnetic field measurement
Environmental class	II
Height	50 mm
Length	170 mm
Max. Operating temperature	55 °C
Max. Transmit range (free field)	100 m
Max. Transmitting range (building)	30 m
Min. operating temperature	-10 °C
Modulation	FM
Mounting location	Windows and French windows
Net weight	1.5 kg
Product group	Detectors
Radio frequency	868.6625 MHz
Radio power	10 mW
Sensor type	Magnetic switch and magnetic field sensor system
Tamper monitoring	Yes
Technology	Electronics
Voltage monitoring	Yes
width	32 mm