

# 19" TFT Color Monitor

Art.-Nr. TVAC10020

Seite 1 von 2



The black 19" TFT monitor in new design offers excellent picture quality and rapid response time for optimal image fidelity. The integrated BNC connection and the wide range of interfaces equip the monitor to meet the challenges of professional video surveillance systems. All settings can be viewed effortlessly on the multilingual On-Screen Display (OSD). The configuration also includes an integrated loudspeaker and audio input/output, as well as automatic signal detection and a 2D comb filter for a softer and clearer image without the disruptive Dot Crawl Effect.

## Technologies

- Fast response time (5 ms)
- High resolution: 1280 x 1024 pixels
- Graphical on-screen display (OSD)
- Integrated loudspeaker
- Inputs: 1 x VGA, 1 x BNC, 1 x cinch (audio)
- Outputs: 1 x BNC, 1 x cinch (audio)

## Technical data - 19" TFT Color Monitor

Brightness	250 cd/m <sup>2</sup>
Colour levels	16,2
Comb filter	2D
Connections	VGA, 2 x BNC, Audio-Cinch In&Out
Contrast ratio	800:1
DC voltage supply	12 V
Dimensions	(WxHxD) 425x415x240 mm
Display surface	Matte
Height	415 mm
Housing material	Plastic

# 19" TFT Color Monitor

Art.-Nr. TVAC10020

Seite 2 von 2

## Technical data - 19" TFT Color Monitor

Image format	4:3
Length	240 mm
Loudspeaker	Integrated 2x0.5 W
Max. humidity	80 %
Max. operating temperature	60 °C
Min. operating temperature	0 °C
Monitor type	TFT standard
Net weight	4,5 kg
OSD language	multilingual
Power consumption	2.750 mA
Reaction time	5 ms
Screen diagonal	19 in
Signal detection	Automatic
Video system	PAL / NTSC
Viewing angle horizontal/vertical	170/160
Width	425 mm