

# CCTV Performance Power Supply 5 A

Art.-Nr. TVAC35520

Seite 1 von 2



The CCTV performance power supply transforms 230 VAC into 13.8 VDC. It is therefore ideal to serve as central power supply station for video surveillance systems. The device provides 8 separate connections.

The CCTV performance power supply works with both 230 V AC mains power and a 12V/7Ah standby battery (BT2070). The charging electronics for the battery is integrated in the robust metal housing of the CCTV power supply unit. The output current (nominal current) is 5 A. This switching power supply is low in power consumption and high in efficiency.

The performance power supply unit is designed for indoor use. A lid contact allows monitoring the device and protecting it from potential tampering activities. Pre-cut perforations on the side of the housing enable customized openings for tidy wiring. The LED control indicator informs you constantly about the state of the power supply unit. The 8 outputs are individually fused and protected from overload and short-circuit.

## Technologies

- Regulated 13.8 V DC output signal
- Electronic overload protection
- Additional 1.0 charging current for backup battery (with holding charge)
- LED control indicators for mains and fuse
- Rugged metal housing

# CCTV Performance Power Supply 5 A

Art.-Nr. TVAC35520

Seite 2 von 2

## Technical data - CCTV Performance Power Supply 5 A

|                          |   |
|--------------------------|---|
| AC voltage supply        | 230 V   |
| Charging electronics     | 12 / 7 V/Ah   |
| Dimensions               | (W x H x D) 338 x 281 x 86 mm                             |
| Emergency battery        | BT2070 (optional)   |
| Fuse protection outputs  | 8 x F5.0 A  |
| Height                   | 281 mm  |
| Housing material         | metal   |
| Length                   | 86 mm   |
| Material type            | Metal housing   |
| Net weight               | 3,4 kg  |
| Operating current        | 5.000 mA  |
| Output                   | 8   |
| Output voltage DC        | 13,4 – 14,2 on main supply / 10,0 – 12,3 battery supply V |
| PSTI conformity required | No  |
| Sabotage monitoring      | Cover switch  |
| Width                    | 338 mm  |