



Art.-Nr. TVAC50030 Seite 1 von 2



The 22" TFT color monitor of the Profiline series has been especially designed for the high demands of professional video surveillance. The integrated quad processor and its range of connections (inputs: 4x BNC, 1x VGA, 1x HDMI, 1x Audio, 4x Alarm, outputs: 4 x BNC) make it a multitalented monitor, suitable even for complex video systems. In addition to the excellent image representation with high brightness, 3D comb filter and rapid response time, the monitor also impresses with its special security functions. In the event of an alarm being triggered, a pop-up with the image of the relevant camera appears on the monitor. Furthermore, display functions such as Picture-in-Picture and Picture-over-Picture can be used. The Profiline monitor is assemled into a stable metal frame.

Technologies

- Integrated quad processor
- Pop-up upon alarm triggering
- Very bright (500 cd/m2)
- 4 BNC and 4 alarm inputs
- HDMI and VGA input
- Resolution: 1680 x 1050 (WSXGA+)

Technical data - 22" Quad TFT Color Monitor Profiline

| Brightness | 500 cd/m ² |
|-------------------|--|
| Colour levels | 16,7 |
| Comb filter | 3D |
| Connection type | 4x BNC, 1x VGA, 1x HDMI, 4x Alarm-Eingänge, 1x Audio |
| Contrast ratio | 1000:1 |
| DC voltage supply | 12 V |
| Dimensions | (WxHxD) 532x427x200 mm |
| Functions | PIP, POP, Alarm pop-up |
| Height | 427 mm |
| Housing material | Metal |



22" Quad TFT Color Monitor Profiline

Art.-Nr. TVAC50030 Seite 2 von 2

Technical data - 22" Quad TFT Color Monitor Profiline

| Image format | 16:10 |
|----------------------------|------------------|
| Length | 200 mm |
| Loudspeaker | Integrated 2x2 W |
| Max. humidity | 85 % |
| Max. operating temperature | 40 °C |
| Min. operating temperature | 0 °C |
| Monitor type | Quad monitor |
| Net weight | 6,5 kg |
| OSD language | multilingual |
| Power consumption | 5 W |
| Reaction time | 5 ms |
| Screen diagonal | 22 in |
| Signal detection | Automatic |
| Video system | PAL / NTSC |
| Viewing angle | 170/170 |
| horizontal/vertical | |
| Width | 532 mm |