

# Outdoor Housing for IP P/T Cameras

Art.-Nr. TVAC70000

Seite 1 von 1



With this outdoor housing, you can also use your pan/tilt network camera outdoors. The housing is dust-proof and protected against strong jets of water (IP66). It protects your mobile network camera for outdoor use reliably against wind and weather. A 12 VDC heater is integrated into the housing which prevents the glass dome from steaming up and the formation of condensation. The result: Clear vision whatever the outside temperature or weather. The housing is available for LAN cameras (TVAC70000) and WLAN cameras (TVAC70050). Connecting the LAN camera which is protected by housing to the network is easy and quick by hand: The LAN cable can be fed outwards to the housing opening on the side or on the base plate (3 m UV protected LAN cable supplied, further cabling by means of a connector). Important instructions: Outdoor housing not suitable in combination with activated IR light.

## Technologies

- Suitable for pan/tilt network cameras
- 12 V DC heating
- Protection class IP66
- Not suitable in conjunction with activated IR light

## Technical data - Outdoor Housing for IP P/T Cameras

|                            |                    |
|----------------------------|--------------------|
| Cabling                    | internal           |
| Dimensions                 | (WxHxD) 160x165 mm |
| Heating                    | 12 VDC / 680mA     |
| Height                     | 165 mm             |
| IP protection class        | 66                 |
| Max. operating temperature | 50 °C              |
| Min. operating temperature | -10 °C             |
| Net weight                 | 1,6 kg             |
| Width                      | 160 mm             |