

Vandal-proof IR 550 TVL outdoor dome camera

Art.-Nr. TVCC36500

Seite 1 von 2



Technologies

- 550 TVL resolution
- Light-sensitive chip set for clear image display under poor light conditions
- Integrated 3.6 mm fixed-focus lens
- Plug & play with mounting plate for quick installation
- 3-axis camera mount
- Weatherproof camera housing (IP66)

Technical data - Vandal-proof IR 550 TVL outdoor dome camera

| | |
|--|---|
| Amplifier control | AGC |
| Aperture at minimum illumination (IR) | 2 |
| Aperture at minimum illumination (color) | 2.0, 5 |
| Backlight compensation | BLC |
| Camera type | Outdoor dome camera |
| Certifications | CE, RoHS, Reach |
| Connections | 2 x BNC, Cinch, DC (5.5x2.1mm) |
| Current consumption | 460 mA |
| DC power supply | 12 V |
| DSP | Sharp |
| Day/night switching | IR cut can be swivelled electromagnetically |
| Dimensions | (HxØ) 102 x145 mm |
| Electronic shutter | AES |
| Focal length | 3,6 mm |

Vandal-proof IR 550 TVL outdoor dome camera

Art.-Nr. TVCC36500

Seite 2 von 2

Technical data - Vandal-proof IR 550 TVL outdoor dome camera

| | |
|------------------------------|--------------------------|
| Height | 102 mm |
| Horizontal viewing angle | 71 ° |
| IR LEDs | Yes |
| IR range (up to) | 20 m |
| Image sensor | 1/3" Sharp HQ CCD |
| Lens | 3.6 |
| Max. Air humidity | 85 % |
| Max. Operating temperature | 50 °C |
| Min. operating temperature | -10 °C |
| Minimum illumination (IR) | 0 lx |
| Minimum illumination (color) | 0.03 lx |
| Net weight | 0.46 kg |
| Number of IR LEDs | 24 |
| Picture elements (total) | 795(H) x 596(V) |
| Pixels (effective) | 752(H) x 582(V) |
| Protection class IP | 66 |
| Signal-to-noise ratio | >48 dB |
| TVL | 550 |
| Video output | 2 x FBAS (1 Vss, 75 Ohm) |
| Video system | PAL |
| WEEE group | 09 |
| White balance | AWB |
| width | 145 mm |