

Day/Night PTZ 560 TVL Dome camera

Art.-Nr. TVCC75100

Seite 1 von 2

Technologies

- 1/4" Interline Transfer CCD
- 27 x motor zoom lens
- Ultra-quiet camera mechanics with 0.024° accuracy
- 16 x digital zoom
- Privacy masking

Technical data - Day/Night PTZ 560 TVL Dome camera

AC power supply	18 - 32 V
Alarm input (NO/NC)	4
Article program	Professional
Backlight compensation	BLC
Camera type	PTZ domecamera
Current consumption	850 mA
DSP	Samsung
Day/night switching	Mechanically swivel IR filter
Dimensions	147 x 190 mm
Focal length	3,5-95,0 mm
Height	190 mm
Horizontal viewing angle	55,5-2,24 °
Image sensor	1/4" Interline Transfer CCD
Language OSD	Deutsch, Englisch, Französisch, Niederländisch, Dänisch
Lens	3.5 - 95.0
Max. Operating temperature	50 °C
Min. operating temperature	-10 °C
Minimum illumination (color)	0.2 lx
Minimum lighting (B/W)	0.02 lx
Net weight	2.107 kg
Noise suppression	2D DNR
Number of presets	165
Number of tours	8
Pan/tilt range	360°/180°
Product group	Video
Protection class IP	34
Protocols	Pelco-D
Signal-to-noise ratio	>50 dB
TVL	560

Day/Night PTZ 560 TVL Dome camera

Art.-Nr. TVCC75100

Seite 2 von 2

Technical data - Day/Night PTZ 560 TVL Dome camera

Video output	1Vss / 75 Ohm / BNC plug connector
WEEE group	09
White balance	AWB
width	147 mm