

SLT Standard stainless steel

Art.-Nr. 501595

Seite 1 von 2

This SLT series electronic security fitting ensures increased intrusion protection and more convenient access, and enables keyless opening thanks to code entry. It is operated by entering a code on the coverable keypad or by using the ABUS Seccor chip key as usual. Entering a valid code on the keypad enables keyless entry and is a safer option in case the key is lost or the door slams shut unexpectedly. The protocol and time function makes it possible to save events and allocate rights linked to the time of day or the day of the week. The fitting has additional plating for even greater protection against break-ins.

Technologies

- Mechatronic security fitting with code keypad, chip key reader and logging function
- Increased security for your front door: Intrusion protection and security in case of key loss and accidental closing of the front door
- Convenient and flexible door opening thanks to code entry
- Acoustic signal

Technical data - SLT Standard stainless steel

Alphanumeric keypad	Yes
Annual profiles	No
Areas of application	Doors with a PZ mortise lock and lever
Closing media	ABUS Seccor chip key
Colour	Stainless steel
Combination code	Yes
Comfort locking	Yes
Drill protection	Security
Electronics	Default
Emergency power supply	ESE (see general accessories)
Emergency power supply possible	Yes
Event memory	No
Language Manual	EN
Language OSD	English
Language Packaging	EN
Material	Die-cast zinc
Max. Air humidity	80 %
Max. Max. number of locking media	511
Max. Operating temperature inside	60 °C

SLT Standard stainless steel

Art.-Nr. 501595

Seite 2 von 2

Technical data - SLT Standard stainless steel

Max. Operating temperature outside	60 °C
Min. operating temperature inside	-10 °C
Min. operating temperature outside	-20 °C
Net weight	2.808 kg
Number of cycles/battery	50,000
Number of keypad codes	4-digit to 6-digit
Permanent access	Yes
Programming 1	Per Prog ACS or PELT + Prog ACS or SKM
Protocol and time function	No
Reader type	Chip key reader and code entry
WEEE group	09
Weekly profiles	No
ZAAP	No
signaling	Audible