

# Secvest 2WAY Wireless Remote Control

Art.-Nr. FU8100

Seite 1 von 2



The bi-directional Secvest 2WAY wireless remote control is an optional accessory for the Secvest 2WAY. You can use it to control your system by the press of a button. In addition, you can query the current status of the system. With the remote control, you can conveniently arm and disarm the alarm system, receiving immediate feedback about the changed system status via the integrated LEDs. Simultaneously pressing and holding the arming button and the disarming button triggers a panic alarm. Pressing the third button queries all important information about the status of your alarm center (armed, disarmed, internally armed, fault). Feedback is also sent immediately and directly to your remote control. The fourth button can be freely programmed. In addition to the internal arming, you can use this for activating an output (e.g. for controlling a garage door). The fourth button is programmed on the Secvest 2WAY. The range of the Secvest 2WAY wireless remote control is approx. 30 meters.

## Technologies

- For convenient operation of the system
- Reporting and display of the current system status
- Freely programmable fourth button (Secvest 2WAY only)
- Manual panic alarm possible (Secvest 2WAY only)

## Technical data - Secvest 2WAY Wireless Remote Control

Battery - max. battery life	2 y
Battery - type	Lithium battery / CR 2450 Li-Mn 3V
Certifications	INCERT, VSÖ, F&P, NCP
Dimensions	(HxD) 15x50 mm
Display	Yes
Environmental class	II
Height	15 mm
Housing material	ABS

# Secvest 2WAY Wireless Remote Control

Art.-Nr. FU8100

Seite 2 von 2

---

## Technical data - Secvest 2WAY Wireless Remote Control

Max. humidity	94 %
Max. operating temperature	55 °C
Max. receiving range (building)	10 m
Max. transmission range (building)	30 m
Min. operating temperature	-10 °C
Net weight	0,03 kg
PSTI conformity required	No
Radio frequency	868,6625 MHz
Radio power	10 mW
Voltage monitoring	Yes
Width	50 mm