

Indoor IP Camera + Accessory

Art.-Nr. TVVR36100S

Seite 1 von 2

Technical data - Indoor IP Camera + Accessory

Alarm input (NO/NC)	1
Alarming	E-Mail
Audio	64Kbps(G.711)/16Kbps(G.726)/32-128Kbps(MP2L2)
Backlight compensation	BLC, DWDR
Camera type	Day/night
Certifications	CE, RoHS, Reach
DC voltage supply	12 V
Day/night switching	ICR
Electronic shutter	1/25 s - 1/100,000 s
Encryption	HTTPS SSLv3, WEP 64/128bit, WPA/WPA2-PSK
Focal length	4 mm
Frame rate	50Hz: 25fps (1280 x 960), 25fps (1280 x 720); 60Hz: 30fps (1280 x 960), 30fps (1280 x 720)
Height	139 mm
Horizontal viewing angle	75,8 °
IP protection class	34
IR LEDs	Yes
Image sensor	1/3" Progressive Scan CMOS
LAN network access	RJ45
Length	71 mm
Lens	F2.0, 4.0
Max. operating temperature	50 °C
Max. resolution @ frame rate	1280 × 720 @ 30 fps
Microphone	Yes
Min. operating temperature	-10 °C
Minimum illumination (colour)	1 lx
Motion detection	3 zones
Network camera protocols	Bonjour, TCP/IP, DHCP, PPPoE, ARP, ICMP, FTP, SMTP, DNS, NTP, UPnP, RTSP, RTP, HTTP, TCP, UDP, 3GPP/ISMA RTSP
Number of users	6
ONVIF	Profile S
PIR range	10 m
Power consumption	450 mA
Pre/post alarm memory	Yes
Relay output	1
Resolution modes	1280 x 960; 1280 x 720
Software	ABUS VMS, Internet Explorer 6, Safari, Mozilla Firefox

Indoor IP Camera + Accessory

Art.-Nr. TVVR36100S

Seite 2 von 2

Technical data - Indoor IP Camera + Accessory

Storage medium	microSD (64 GB)
Supported browsers	Internet Explorer 6, Safari, Mozilla Firefox, Google Chrome
Technology	IP
Video compression	H.264, MJPEG
WLAN network access	802.11 b/g/n
White balance	AWB
Width	66 mm