

# Analogue HD Monitoring Set: 8-Channel Video Recorder + 4 Outdoor Dome Cameras

Art.-Nr. TVVR33418

Seite 1 von 3



## Everything in one package

This analogue HD package contains everything you need for analogue wired video surveillance with recording in HD resolution. The 8-channel recorder including a 1 TB hard disk drive can record approx. 2 weeks of 24-hour video data from the 4 supplied outdoor dome cameras. The system can be extended to max. 8 cameras if necessary.

## Connect and record

The set is directly preconfigured for use: mount the cameras, connect and then select the desired recording mode (when motion is detected, according to a schedule or continuous recording). The image data can be viewed live and in real time using an additionally connected monitor. The set is operated intuitively using the supplied USB mouse.

## Secure 24-hour surveillance

Thanks to automatic day/night switching, the cameras are suitable for 24-hour surveillance in outdoor areas. The 24 LEDs have a range of 10 m for increased security and are suitable for operation in unprotected outdoor areas due to their IP66 protection class. The design of the dome cameras is especially good for protecting them against vandalism.

## Full HD-ready

The supplied recorder is Full HD-ready and can record video data in 1080p resolution at 12 frames per second. The set is therefore ideal for upgrading existing analogue systems to HD or Full HD. The set can also be extended by 4 additional cameras, e.g. with existing analogue cameras for use in the same system or extra analogue HD cameras.

The effective IR range will depend on the installation location. If there are surfaces that absorb light or no objects that reflect IR light in the field of view, the IR range will be reduced and/or the video image will be too dark. Reflective objects in the immediate vicinity of the camera (e.g. roof gutter or wall) may also result in the reflection of IR light, which can disturb the image.

With the HDCC31500 & HDCC32500 models, it is important to ensure that the IR LEDs are not covered by the camera cap, as this could cause reflections.

## Technologies

# Analogue HD Monitoring Set: 8-Channel Video Recorder + 4 Outdoor Dome Cameras

Art.-Nr. TVVR33418

Seite 2 von 3

- Complete set with 8-channel recorder, 4 outdoor dome cameras, 1 TB hard disk drive, 5 power supply units and accessories
- Incl. 1 TB hard disk drive for approx. 2 weeks of continuous recording
- Simple and intuitive operation using a mouse
- Live display and recording in real-time and in HD resolution (720p)
- Recording via motion detection, following a time schedule or continuously
- Automatic day/night switching for analogue HD 720p outdoor dome cameras
- Recorder compatible with analogue HD and analogue cameras
- Simple connection of cameras using a standard coaxial cable (BNC connector)
- Full HD Ready (1080p): recording and playback at 12 frames per second
- Ideal for upgrading old analogue systems to HD or full HD resolution

## Technical data - Analogue HD 720p Outdoor Dome Camera

Backlight compensation	Yes
Camera outputs	1 x BNC (HD-TVI)
Camera type	Analogue HD 720p Outdoor Dome Camera
Certifications	CE, C-Tick
Connections	Video signal (BNC), power supply (DC)
DC voltage supply	12 V
Day/night switching	Electromechanical IR cut filter
Diameter	89,6 mm
Dimensions	89,6 x 59,1 mm
Electronic shutter	1/25 ~ 1/50.000
Focal length	3,6 mm
Height	59,1 mm
Horizontal viewing angle	76,88 °
Housing material	metal
IP protection class	66
IR LEDs	24
IR range (up to)	10 m
Image sensor	1/3 inch progressive scan CMOS
Language of instructions	English, German, French, Dutch, Danish, Italian, Polish, Spanish, Swedish
Language packing	English, German, French, Dutch, Danish, Italian, Polish, Spanish, Swedish
Lens	3.6 mm, fixed lens
Max. humidity	90 %
Max. operating temperature	50 °C
Max. resolution @ frame rate	1280 x 720 @ 25 fps (PAL) / 1280 x 720 @ 30 fps (NTSC)
Min. operating temperature	-20 °C
Minimum illumination (IR)	0 lx

# Analogue HD Monitoring Set: 8-Channel Video Recorder + 4 Outdoor Dome Cameras

Art.-Nr. TVVR33418

Seite 3 von 3

## Technical data - Analogue HD 720p Outdoor Dome Camera

Minimum illumination (colour)	0,01 lx
Net weight	0,4 kg
Noise reduction	> 52 dB
Pixels (effective)	1280 (H) x 720 (V) pixel
Power consumption	300 mA
Resolution modes	720
Technology	HD-TVI
Video system	HD-TVI
Width	89,6 mm
EAN	4043158065886

## Technical data - 30 m Preassembled Video Combination Cable

Cable length	30 m
Cable type	Combined video cable
Connection type	BNC (male) – BNC (female)
DC voltage supply	12 V
Damping	0,53 dB
Diameter	6 mm
Housing material	PVC
Insulation	PE
Intended use	indoors
Length	30.000 mm
Max. operating temperature	60 °C
Min. operating temperature	-10 °C
Outer diameter	6 mm
EAN	4043158022049

## Technical data - 2,5" Internal Hard Disk Drive with 1 TB Capacity

Connections	S-ATA
Dimensions	70 x 10 x 100 mm
Height	10 mm
Length	100 mm
Max. operating temperature	60 °C
Min. operating temperature	0 °C
Net weight	0,095 kg
Power consumption	1,4 W
Storage capacity	1.000
Width	70 mm
EAN	4043158063196