

17" LED Monitor with BNC input

Art.-Nr. TVAC10012

Seite 1 von 3



The 17" LED monitor offers outstanding picture quality and rapid reaction times for optimum picture fidelity. With integrated BNC connections and other interfaces, the monitor is well-equipped for the requirements of professional video surveillance. The signal is detected automatically and all settings can easily be configured in the on-screen display (OSD) in several languages. Thanks to energy-saving LED technology, the monitor has a low power consumption, and therefore can be used efficiently for 24/7 operation.

Detailed surveillance pictures

With its high resolution, outstanding picture fidelity and rapid reaction time, the monitor produces accurate surveillance pictures. The LED backlighting ensures optimum contrast and an extremely realistic colour display. With the picture-in-picture and picture-over-picture functions, multi-tasking is quick and simple. With the aid of picture-in-picture, a small preview window can be conveniently displayed.

Versatile connections

The HDMI, VGA and BNC video inputs offer flexibility for connecting the monitor to a recorder, live cameras or a computer. Integrated loudspeakers and audio inputs also allow sound signals to be played back. All of these features make the monitor a cost-effective component for versatile surveillance and IT systems.

Efficient uninterrupted 24/7 use

Thanks to high-quality industry components, the monitor is optimally suited for uninterrupted 24/7 use. The energy-efficient LED display ensures very low power consumption.

17" LED Monitor with BNC input

Art.-Nr. TVAC10012

Seite 2 von 3

Easy installation

VESA standard mounts allow mounting to a wall or ceiling. This makes installation fast and easy.

Technologies

- Resolution: 1280 x 1024 pixels
- Fast reaction time (5 ms)
- LED background lighting: brilliant colour display and contrast
- Graphical on-screen display (OSD)
- Connections: HDMI, VGA, S-Video, 2 x BNC in/out, 2 x cinch (audio), PC audio input
- Integrated loudspeaker
- Low power consumption (LED technology)
- For wall and ceiling installation (with VESA mount)

Technical data - 17" LED Monitor with BNC input

Brightness	250 cd/m ²
Certifications	CE
Colour levels	16,7
Comb filter	3D
Connections	1 x HDMI, 1 x VGA, 2 x BNC, 1 x PC Audio, 2 x Chinch Audio, 2 x BNC Out
Contrast ratio	1.000:1
DC voltage supply	12 V
Dimensions	372 x 370 x 50 mm
Display surface	matte
Gross weight	4,6 kg
Height	370 mm
Housing material	Plastic
Image format	5:4
Input	1 x HDMI, 1 x VGA, 2 x BNC, 1 x PC-Audio, 2 x Chinch-Audio
Length	50 mm
Loudspeaker	2 x 2,5 W
Max. humidity	70 %
Max. operating temperature	45 °C
Min. operating temperature	0 °C
Monitor type	LED
Net weight	3,3 kg
Output	2 x BNC
Power consumption	2 mA
Reaction time	5 ms
Screen diagonal	17 in

17" LED Monitor with BNC input

Art.-Nr. TVAC10012

Seite 3 von 3

Technical data - 17" LED Monitor with BNC input

Signal detection	Automatic
Video system	PAL / NTSC
Viewing angle horizontal/vertical	170° x 160°
Width	372 mm