

12-Channel TV Wall Decoder

Art.-Nr. TVAC26120

Seite 1 von 1

Technical data - 12-Channel TV Wall Decoder

AC power supply	100 - 240 V
Audio input	1 x 3,5mm (2.0Vp-p, 1K0hm)
Audio output	1 x 3,5mm (2.0Vp-p, 1K0hm)
Certifications	CE, C-Tick, FCC
Connectable devices	ABUS CMS, ABUS NVR, ABUS DVR, ABUS IP-Kameras
Dimensions	440 x 340 x 88 mm
Gross weight	7 kg
Height	88 mm
LED display	Power LED, Link LED, RX/TX LED
Language Manual	English
Language OSD	English
Length	340 mm
Max. Air humidity	90 %
Max. Operating temperature	55 °C
Min. operating temperature	-10 °C
Monitor outputs	12 x DVI-I (analogue + digital)
Net weight	6.2 kg
Network connection	1 x RJ45 10/100/1000 Mbps
Number of streams	5
Power consumption	90 W
Product group	Accessories
Resolution live view	1920x1080@50hz, 1920x108@60Hz, 1600x1200@60Hz, 1280x1024@60Hz, 1280x720@50Hz, 1280x720@60Hz, 1024x720@60Hz
width	440 mm