

Signal Amplification Kit

Art.-Nr. TVAC17520

Seite 1 von 2



This complete kit including 5 dB antenna, wall mount and 2 m cable is ideal for improving signal strength and extending the range of wireless and Wi-Fi cameras. The sturdy wall mount, weather-protected cable and weather-protected antenna enable smooth installation. The antenna is compatible with all RP-SMA connections with a fine thread (45 threads per inch).

Suitable for TVAC14010, TVAC15010, TVAC1601x, TVAC18010, TVAC19x00, PPIC3xxxx, PPDF1xxxx.

Technologies

- Complete kit including 5 dB antenna, wall mount and 2 m cable
- Ideal for improving signal strength and extending the range of wireless and Wi-Fi cameras
- Sturdy wall mount and weather protected cable and antenna
- Suitable for TVAC14010, TVAC15010, TVAC1601x, TVAC18010, TVAC19x00, PPIC3xxxx, PPDF1xxxx

Technical data - Signal Amplification Kit

| | |
|----------------------------|----------------------|
| Cable diameter | 6 mm |
| Cable length | 2 m |
| Connections | SMA plug |
| Dimensions | (ØxH) 30x320 mm |
| Gain | 5 dB |
| Height | 320 mm |
| Impedance | 50 Ω |
| Intended use | Indoors and outdoors |
| Max. operating temperature | 60 °C |
| Min. operating temperature | -30 °C |
| Net weight | 0,29 kg |
| Opening angle hori. | 360 ° |
| Power consumption | 10 W |

Signal Amplification Kit



Art.-Nr. TVAC17520

Seite 2 von 2

Technical data - Signal Amplification Kit

| | |
|-------|-------|
| Width | 30 mm |
|-------|-------|