

Secvest Wireless Outdoor Motion Detector

Art.-Nr. FUBW50022

Seite 1 von 2

Robust detector for reliable motion detection

The Secvest wireless outdoor motion detector reacts to any kind of heat movement and reliably reports this to the Secvest alarm panel. Used as a perimeter warning, it monitors the outside area of your home. As soon as someone enters the detector's monitored area, an outdoor sounder can transmit a warning signal. This means that potential intruders can be deterred early on.

Versatile use

The integrated PIR elements can be swivelled by 180° and tilted by 90° so that the detector can be used in almost any location. The detection range - depending on installation height - is up to 30 metres.

Technologies

- Outdoor motion detector for perimeter surveillance
- With dual-infrared element
- Detection range of up to 30 m
- Protection class IP55

Technical data - Secvest Wireless Outdoor Motion Detector

Battery - max. battery life	2 years(s)
Battery type	CR123
Certifications	conform according to EN 50131-1
Compatible with	Secvest, Terxon, BUM060040
Cover monitoring	No
Depth	115 mm
Detection area detector (m)	11 – 30 m
Detection method	Heat recognition
Dimensions	(BxHxT) 155x120x115 mm
Environmental class	IV
Gross weight	0.88 kg
Height	120 mm
Housing material	Polyethylene HDPE
Language Manual	DE, UK, FR, NL, DK
Language Packaging	DE, UK, FR, NL, DK, PL, SE, ES
Length	115 mm
Max. Air humidity	75 %
Max. Operating temperature	55 °C
Max. Transmit range (free field)	100 m

Secvest Wireless Outdoor Motion Detector



Art.-Nr. FUBW50022

Seite 2 von 2

Technical data - Secvest Wireless Outdoor Motion Detector

Max. Transmitting range (building)	30 m
Mechanical protection	No
Min. operating temperature	-20 °C
Modulation	FM
Net weight	0.332 kg
PSTI conformity needed	No
Product group	Detectors
Protection class IP	55
Pulse selector switch	Yes
Radio frequency	868 MHz
Sensor type	Independent duplex PIR unit
Status display	LED
Tamper monitoring	Yes
Technology	Electronics
Type of protection	Intrusion protection
VdS class	none
Voltage monitoring	Yes
WEEE group	09
width	155 mm