

# ABUS Analogue HD Video Surveillance 2MPx mini tube camera

Art.-Nr. HDCC42560

Seite 1 von 3



The mini tube camera provides high-resolution images in HD 1080p and is easily connected to a recorder using a conventional analogue combined video cable (image and power).

## Reliable data transmission at high resolution

Analogue HD cameras offer the best of both worlds, providing secure, problem-free transmission - knowledge of IPs not required - via analogue combined video cable, and also HD resolution with 1920 x 1080 pixels at 25 frames per second, a performance otherwise matched by megapixel cameras from IP technology. And all of this at an attractive price-performance ratio.

## Weatherproof day/night surveillance

The camera is installed in a robust housing with IP66 protection class and is therefore ideal for outdoor use in all kinds of weather. The integrated IR LEDs and automatic day/night switching provide reliable surveillance day and night. The integrated noise reduction also ensures that the camera produces sharp images even in low lighting conditions.

## Easy commissioning

# ABUS Analogue HD Video Surveillance 2MPx mini tube camera

Art.-Nr. HDCC42560

Seite 2 von 3

Thanks to the supplied combined cable and plug-and-play installation, the camera can be mounted on the ceiling or wall and started up immediately. Even existing BNC cabling can be used.

The effective IR range depends on the installation location. If there are surfaces that absorb light or no objects that reflect IR light in the field of view, the IR range will be reduced and/or the video image will be too dark. Reflective objects in the immediate vicinity of the camera (e.g. roof gutter or wall) may also result in the reflection of IR light, which can disturb the image.

## Technologies

- 2 MPx camera for indoors and outdoors
- Detailed full HD (2MPx) resolution of 1920 x 1080 pixels at 25 frames/second
- Integrated IR LEDs for optimal night vision
- Sturdy weatherproof camera housing (IP66)
- Noise reduction (DNR) for clear images even at low light levels
- Automatic day/night switching
- Can be mounted on ceilings and walls
- Including 1 x 30 m combined video cable (video signal + power supply)
- Plug&Play installation and connection using a BNC connector, including for existing analogue cables

## Technical data - ABUS Analogue HD Video Surveillance 2MPx mini tube camera

Aperture	F1.2
Colour	White
Compatible with	TVVR33xxxxx / HDCC9xxxx
Compatible with Secvest	No
Compatible with Smartvest	No
Compatible with wAppLoxx	No
DC voltage supply	12 V
Day/night switching	Auto
Dimensions	( $\emptyset$ x L) 70 x 149,5 mm
Focal length	2,8 mm
Gross weight	1,29 kg
Horizontal viewing angle	103 °
Housing material	Metal
IP protection class	66
IR LEDs	Yes
IR range (up to)	20 m
IR swivel filter	Yes

# ABUS Analogue HD Video Surveillance 2MPx mini tube camera

Art.-Nr. HDCC42560

Seite 3 von 3

## Technical data - ABUS Analogue HD Video Surveillance 2MPx mini tube camera

Image sensor	1/2.8" CMOS
Lens mount	M12
Max. humidity	90 %
Max. operating temperature	60 °C
Max. resolution @ frame rate	1920 x 1080 @ 25/30 fps
Min. operating temperature	-40 °C
Minimum illumination (IR)	0 lx
Minimum illumination (colour)	0,01 lx
Net weight	0,87 kg
Noise reduction	DNR
Optical Wave Length	850 nm
Power consumption	4 W
Technology	Analog HD
Video output	1x BNC (HD-TVI)