

IP Mini Tube 4 MPx (2.8 mm)

Art.-Nr. IPCB64510A

Seite 1 von 4



Discreet 4 MPx 24/7 outdoor surveillance

Due to its compact dimensions, the IP Mini Tube is a discreet surveillance camera for outdoor and indoor use. The tube is available in several versions with different fixed lenses from 2.8 mm (IPCB64510A) to 4 mm (IPCB64510B) and even 6 mm (IPCB64510C).

The IP Mini Tube provides video streams in 4 MPx resolution with up to 30 fps. The weatherproof IP67 housing allows outdoor use. Due to integrated IR LEDs, the camera can be also used day and night. Access to the camera is possible at any time via app.

3 lens variants for maximum flexibility

The IP Mini Tube is available in 3 versions with different fix lenses. Therefore, the camera offers maximum flexibility in the planning and installation of video surveillance projects. The IP Mini Tube IPCB64510A with a 2.8 mm fixed lens and a horizontal viewing angle of 109 ° is ideal for wide-angle surveillance scenes. The IP Mini Tube IPCB64510C with a 6 mm fixed lens and a horizontal viewing angle of 53 ° is a popular variant for installation in corridors.

Recording and compatibility

The recording can be done either on an ABUS recorder, 3rd party video management software or locally on a microSD card. Furthermore, the camera is compatible with the ABUS Secvest alarm center and the ABUS access control system wAppLoxx.

Comfortable installation

IP Mini Tube 4 MPx (2.8 mm)

Art.-Nr. IPCB64510A

Seite 2 von 4

The IP Mini Tube is mounted on the ceiling or optionally on the wall. We recommend the ABUS installation box (TVAC31480), which allows a protected cabling to wall or ceilings. The free “ABUS IP Installer” software is available for simple setup in the network. The software finds the camera quickly and easily within the network and supports during the installation process.

Note: The camera does not come with a power supply, as it can be powered via PoE.

The effective IR range will depend on the installation location. If there are surfaces that absorb light or no objects that reflect IR light in the field of view, the IR range will be reduced and/or the video image will be too dark. Reflective objects in the immediate vicinity of the camera (e.g. roof gutter or wall) may also result in the reflection of IR light, which can disturb the image.

Technologies

- 4 MPx Resolution: 2.688 x 1.520 @ 30 fps
- 2.8 mm fixed lens
- Ultra low-light performance for excellent results in low-light environments
- 120 dB WDR function to compensate for image contrasts
- Weather protected housing (IP67)
- IR LEDs (range up to 10m)
- Supports H.264, H.265, MJPEG (incl. dynamic GOP)
- microSD card slot for internal data storage
- 12 V DC & PoE (802.3af)

Technical data - IP Mini Tube 4 MPx (2.8 mm)

| | |
|--|-----------------------------|
| Alarm generation | E-Mail, NAS, FTP |
| Aperture at minimum illumination (color) | F1.6 |
| Application purpose | General surveillance |
| Article program | Professional |
| Backlight compensation | WDR, BLC, HLC |
| Camera type | Mini-Tube |
| Colour | RAL9003 |
| Compatible with | NVR, Hybrid DVR, IPCam Plus |
| Compatible with ABUS Link Station | Yes |
| Compatible with Secvest | Yes |
| Compatible with wAppLoxx | Yes |
| Compatible with wAppLoxx Pro | Yes |

IP Mini Tube 4 MPx (2.8 mm)

Art.-Nr. IPCB64510A

Seite 3 von 4

Technical data - IP Mini Tube 4 MPx (2.8 mm)

| | |
|------------------------------|--|
| Connections | 1 x RJ45, 1 x DC |
| Construction type of device | Tube |
| Current consumption | 585 mA |
| DC power supply | 12 (+/-10 %) V |
| Day/night switching | ICR/Color/B/W |
| Dimensions | (LxWxH) 155x74x74 mm |
| Dynamic range (WDR) | 120 dB |
| Electronic shutter | 1/3 - 1/100000 s |
| Encryption | HTTPS |
| Focal length | 2,8 mm |
| Frame rate | 1/16, 1/8, 1/4, 1/2, 1, 2, 4, 6, 8, 10, 12, 15, 16, 18, 20, 22, 25, 30 fps |
| Height | 74 mm |
| Horizontal viewing angle | 109 ° |
| ICR day/night function | Yes |
| IR LEDs | Yes |
| IR range (up to) | 10 m |
| Image optimization | WDR, BLC, HLC, 3D DNR, Vertical Display |
| Image sensor | 1/2.5" Progressive Scan CMOS |
| Language Manual | DE, UK, FR, NL, DK |
| Language OSD | DE, UK, FR, NL, DK |
| Length | 155 mm |
| Lens | Fix |
| Lens mount | M12 |
| Max. Air humidity | 95 % |
| Max. Operating temperature | 60 °C |
| Max. Resolution @ frame rate | 2688 x 1520 @ 30 fps |
| Microphone | No |
| Min. operating temperature | -30 °C |
| Minimum illumination (IR) | 0 lx |
| Minimum illumination (color) | 0.008 lx |
| Motion detection | 8 zones |
| Net weight | 0.55 kg |
| Network bandwidth Video | 32 kBit/s - 16 MBit/s |
| Network camera protocols | IPv4/v6, HTTP, HTTPS, FTP, SMTP, UPnP, DNS, DynDNS, NTP, RTSP, TCP, UDP, DHCP, ONVIF Profile S, ONVIF Profile G, ABUS Server, Secvest Link |
| Network connection | RJ45 |
| Network connection LAN | RJ45 10M/100M self-adaptive |
| Noise suppression | 3D DNR |
| Number of IR LEDs | 10 |

IP Mini Tube 4 MPx (2.8 mm)

Art.-Nr. IPCB64510A

Seite 4 von 4

Technical data - IP Mini Tube 4 MPx (2.8 mm)

| | |
|------------------------------|--|
| Number of streams | 3 |
| Number of users | 32 |
| ONVIF | Profile G, S, T |
| Other functions | Auto Backup Recording, Secvest Connectivity |
| PSTI conformity needed | No |
| Pixels (effective) | 2688(H) x 1520(V) |
| PoE Standard | IEEE 802.3af |
| Power consumption | 7.5 W |
| Privacy zones | 4 |
| Product group | Camera |
| Protection class IP | 67 |
| Radio functions | Scene Change Detection |
| Resolution | 4 MP |
| Resolution modes | Stream 1: 2.688 x 1.520 @ 25 fps, Stream 2: 640 x 480 @ 25 fps, Stream 3: 1.280 x 720 @ 25 fps |
| Simultaneous network access | 6 |
| Storage medium | microSD card, 256 GB (opt.) |
| Supported browsers | IE10, IE11, Mozilla Firefox 30.0+, Chrome 31.0+ |
| Vertical angle of view | 60 ° |
| Video Content Analysis (VCA) | Tripwire Detection, Intrusion Detection |
| Video compression | Stream 1: H.264, H.265, Stream 2: H.264, H.265, MJPEG, Stream 3: H.264, H.265; Dynamic GOP |
| Video system | IP |
| WEEE group | 09 |
| White balance | AWB, Manual |
| width | 74 mm |