

ABUS IP video surveillance 6-Channel Wi-Fi complete set

Art.-Nr. TVVR36510T

Seite 1 von 4

Technical data - ABUS IP video surveillance 6-Channel Wi-Fi complete set

| | |
|------------------------|----------|
| Net weight | 1.215 kg |
| PSTI conformity needed | No |
| WEEE group | 09 |

Technical data - ABUS IP video surveillance 2MPx Wi-Fi mini tube camera

| | |
|------------------------------|--|
| Alarm generation | Email |
| Aperture | F2.0 |
| Automatic aperture control | No |
| Base event | Motion detection |
| Channel width | 20 MHz |
| Colour | White |
| Compatible with | TVVR36xxx / TVVR33xxx / NVRxxxxx |
| Compatible with Secvest | Yes |
| Compatible with Smartvest | No |
| Compatible with wAppLoxx | Yes |
| Construction type of device | Tube |
| DC power supply | 12 V |
| Day/night switching | Auto / Manual / Schedule |
| Dimensions | (\emptyset x L) 70 x 157 mm |
| Encryption | 64/128-bit WEP / WPA/WPA2 / WPA-PSK/WPA2-PSK / WPS |
| Focal length | 2,8 mm |
| Frequency range | 2,4 - 2,4835 GHz |
| Gross weight | 0.778 kg |
| Horizontal viewing angle | 85 ° |
| Housing material | Metal / Plastic |
| IR LEDs | Yes |
| IR range (up to) | 20 m |
| IR swivel filter | Yes |
| Image optimization | BLC / Digital WDR |
| Image sensor | 1/2.8" CMOS |
| Image settings | Brightness / Contrast / Saturation / Sharpness / Mirroring |
| Language OSD | DE / UK / FR / NL / DK / IT / PL / ES / SE |
| Lens mount | M12 |
| Loudspeaker | No |
| Max. Air humidity | 95 % |
| Max. Operating temperature | 60 °C |
| Max. Resolution @ frame rate | 1920 x 1080 @ 25/30 fps |

ABUS IP video surveillance 6-Channel Wi-Fi complete set

Art.-Nr. TVVR36510T

Seite 2 von 4

Technical data - ABUS IP video surveillance 2MPx Wi-Fi mini tube camera

| | |
|------------------------------|---|
| Microphone | No |
| Min. humidity | 10 |
| Min. operating temperature | -30 °C |
| Minimum illumination (IR) | 0 lx |
| Minimum illumination (color) | 0.028 lx |
| Net weight | 0.384 kg |
| Network connection | 1x RJ-45 10/100 Mbit/s self-adaptive Ethernet Anschluss |
| Network connection WLAN | IEEE802.11b/g/n / 11b @ 11Mbit/s / 11g @ 54Mbit/s / 11n @ 150Mbit/s |
| Network protocols | TCP/IP / ICMP / HTTP / HTTPS / FTP / DHCP / DNS / DDNS / RTP / RTSP / RTCP / PPPoE / NTP / UPnP / SMTP / IPv6 |
| Noise suppression | 3D DNR |
| Number of users | 32 |
| Optical wavelength | 850 |
| PSTI conformity needed | No |
| PoE Standard | 802.3af |
| Power consumption | 5.8 W |
| Privacy zones | 4 |
| Protection class IP | 67 |
| Radio range | (Depending on installation) 20 - 50 m |
| Recording modes | Manual / time schedule / motion detection |
| Resolution modes | 1920 x 1080 / 1280 x 960 / 1280 x 720 @ 25/30 fps |
| Sensitivity | 11b: -90dBm / 11g: -75dBm / 11n: -74dBm |
| Software | IPCam Plus (iOS & Android) / iDVR Plus (iOS & Android) / IP Installer |
| Storage medium | MicroSD (max. 128GB) / NAS |
| Supported browsers | Internet Explorer, Edge, Chrome, Firefox, Safari |
| Transmission power | 11b: 17 +/- 1,5dBm / 11g: 14 +/- 1,5dBm / 11n: 12,5 +/- 1,5dBm |
| User levels | 3 |
| Video compression | H.264 / MJPEG |
| WEEE group | 09 |
| White balance | Auto white balance (AWB) / incandescent lamp / warm light / natural light / fluorescent lamp |
| EAN | 4043158140293 |

Technical data - 2,5" Internal Hard Disk Drive with 1 TB Capacity

| | |
|----------------------------|------------------|
| Connections | S-ATA |
| Dimensions | 70 x 10 x 100 mm |
| Height | 10 mm |
| Length | 100 mm |
| Max. operating temperature | 60 °C |
| Min. operating temperature | 0 °C |

ABUS IP video surveillance 6-Channel Wi-Fi complete set

Art.-Nr. TVVR36510T

Seite 3 von 4

Technical data - 2,5" Internal Hard Disk Drive with 1 TB Capacity

| | |
|--------------------------------|--------------------|
| Net weight | 0.095 kg |
| PSTI conformity needed | No |
| Power consumption | 1.4 W |
| Product group | Recording solution |
| Storage capacity | 1,000 |
| Video motion detector included | No |
| WEEE group | 09 |
| width | 70 mm |
| EAN | 4043158063196 |

Technical data - 6-Channel Wi-Fi Video Recorder

| | |
|---|---|
| Alarm generation | OSD signal, email, CMS |
| Article program | Performance |
| Certifications | CE, REACH, Law Sarkozy, C-Tick |
| Control unit | mouse |
| Current consumption | 1,000 mA |
| DC power supply | 12 V |
| DDNS | Yes |
| Data backup | 1 x USB 2.0 |
| Decoding performance (local live view & playback) | 4x 2Mpx, 1x 6Mpx |
| Dimensions | 88 x 165 x 90 mm (W x H x D) |
| Height | 165 mm |
| Housing | Cube |
| Language Manual | English, German, French, Dutch, Danish, Italian, Polish, Spanish, Swedish |
| Language OSD | English, German, French, Dutch, Danish, Italian, Polish, Spanish, Swedish |
| Language Packaging | English, German, French, Dutch, Danish, Italian, Polish, Spanish, Swedish |
| Loi Sarkozy compliant (only valid for FR) | Yes |
| Max. Air humidity | 90 % |
| Max. Operating temperature | 40 °C |
| Max. Resolution @ frame rate | 6MPx @ 25 Fps |
| Max. number of video feeds | 6 |
| Min. operating temperature | 0 °C |
| Mobile access | Yes |
| Monitor outputs | HDMI |
| NTP | Yes |
| Net weight | 0.736 kg |
| Network connection | 1 x RJ45 Router 10/100 Mbps, 3 RJ45 LAN 10/100 Mbps |

ABUS IP video surveillance 6-Channel Wi-Fi complete set

Art.-Nr. TVVR36510T

Seite 4 von 4

Technical data - 6-Channel Wi-Fi Video Recorder

| | |
|--|---|
| Network functions | Live view, playback, data export |
| Operation mode | Triplex |
| PoE connections | 0 |
| Power consumption | 12 W |
| Pre/post-alarm memory | 0–30 / 5–900 |
| Product group | Video |
| Recording modes | Manual, time schedule, motion detection, alarm |
| Resolution HDMI output | 1920 × 1080P / 60Hz, 1600 × 1200 / 60Hz, 1280 × 1024 / 60Hz, |
| Resolution recording @ frame rate per camera | 1920 x 1080 @ 25 fps, 1280 x 720 @ 25 fps, 640 x 480 @ 25 fps, 704 x 576 @ 25 fps, 352 x 288 @ 25 fps |
| Search modes | By event, date and time, S.M.A.R.T. |
| Simultaneous network access | 128 camera connections |
| Storage medium | 1 x 2,5" SATA HDD |
| Supported IP cameras | TVIP1156x, TVIP21560, TVIP41500, TVIP4x560, TVIP41660, TVIP615x0, TVIP6x560, TVIP82900 |
| Synchronized playback | 6 |
| Total frame rate (PAL) | 150 |
| Total network throughput (input/output) | (50/80) Mbits |
| Total video channels | 6 |
| User levels | 2 |
| Video channels HD-SDI | 0 |
| Video channels IP | 6 |
| Video channels analog | 0 |
| Video compression | H.264 |
| Video motion detector included | Yes |
| Views | 1 / 4 / 6 / 8 / 9 |
| WEEE group | 09 |
| Web server | Yes |
| width | 88 mm |
| EAN | 4043158065916 |