

5 m CAT 6A S/FTP PIMF patch cable

Art.-Nr. TVAC40831

Seite 1 von 1

The CAT 6A S/FTP PIMF patch cable offers reliable data transmission for your video surveillance system and can be used universally to connect any network-compatible devices. CAT 6A is designed for fast transmission rates of up to 10 gigabits per second. S/FTP PIMF cables are also characterised by their high-quality double shielding and thus offer protection against external interference and crosstalk.

Technologies

- Twisted-pair cable with RJ45 plug
- Suitable for Ethernet networks up to 10 gigabits per second
- Designed for operating frequencies of up to 500 MHz
- Cores shielded in pairs with metal foil
- The entire cable is additionally provided with braided shielding
- Available in different lengths

Technical data - 5 m CAT 6A S/FTP PIMF patch cable

Cable length	5 m
Cable style	CAT 6A Twisted pair 1:1
Colour	grey
Connection type	RJ45 connector
Cores	4 x 2 x AWG 27/7
Diameter of cores	0.457 mm
Gross weight	0.164 kg
Insulation	PVC
Max. Operating temperature	70 °C
Min. operating temperature	-10 °C
Net weight	0.16 kg
PSTI conformity needed	No
Product group	Accessories
Shielding	S/FTP PIMF
WEEE group	09