Art.-Nr. TVVR36511T

Video surveillance set for continuous monitoring

This complete set makes it easier to install video surveillance indoors or in outdoor areas. The set contains a 6-channel network Wi-Fi video recorder including a built-in hard disk drive with 1TB of storage space for approx. six weeks of continuous recording, one outdoor Wi-Fi cameras, two power supply units and accessories.

Professional recording technology that is easy to operate

Depending on the setting, the recorder starts recording manually, following a time schedule or using a motion sensor. It can be operated conveniently using a mouse or via the ABUS iDVR Plus app. The video images are stored in brilliant quality, only take up a small amount of space on the hard disk drive and have been optimised for quick network access. The IP67 protection class cameras have a WDR function for optimum backlight compensation and are ideal for continuously monitoring outdoor or entrance areas. A total of up to six ABUS cameras (four Wi-Fi + two via the network) can be integrated into the system.

Quick and easy installation

Video recorders and routers are connected using a network cable for installation. As the recorder has its own access point (Wi-Fi hotspot), plug-and-play installation wizard and WPS function, wireless connection of the Wi-Fi outdoor cameras to the video recorder can be carried out quickly and easily. The network cable between the video recorder and router is then only required if external access to the system is to be provided.

Technologies

- Complete set with 6-channel Wi-Fi recorder, 1 Wi-Fi outdoor cameras, 1 TB hard disk drive, 2 power supply units and accessories
- Includes access point for max. four Wi-Fi cameras for simple set-up with a router
- Simultaneous live cast from up to six IP cameras (four Wi-Fi cameras and two network cameras)
- Integrated switch function for connecting home appliances via the LAN port (e.g. printer)





Seite 1 von 4

Art.-Nr. TVVR36511T

Seite 2 von 4

- Outdoor camera with WDR function for backlight compensation, which is ideal for entrance areas
- Compact design and high protection class (IP67) for the Wi-Fi outdoor camera
- Detailed high camera resolution, with 1920 x 1080 pixels at 25 frames/second
- Incl. 1 TB hard disk drive for approx. six weeks of continuous recording
- Recording via motion detection, following a time schedule or continuously
- Mobile access via the ABUS iDVR app

Technical data - 6-Channel Wi-Fi Video Recorder

Alarming	OSD signal, email, CMS
DC voltage supply	12 V
Dimensions	88 x 165 x 90 mm (W x H x D) mm
Housing	Cube
IP video channels	6
Max. humidity	90 %
Max. operating temperature	40 °C
Max. resolution @ frame rate	6MPx @ 25 Fps
Min. operating temperature	0 °C
Net weight	0,68 kg
Network access	1 x RJ45 Router 10/100 Mbps, 3 RJ45 LAN 10/100 Mbps
OSD language	English, German, French, Dutch, Danish, Italian, Polish, Spanish, Swedish
Performance decoding (local	4x 2Mpx, 1x 6Mpx
live view & playback)	
PoE connections	0
Recording modes	Manual, time schedule, motion detection, alarm
Recording resolution @ frame	1920 x 1080 @ 25 fps, 1280 x 720 @ 25 fps, 640 x 480 @ 25 fps, 704 x 576 @ 25 fps,
rate per camera	352 x 288 @ 25 fps
Resolution HDMI output	1920 × 1080P / 60Hz, 1600 × 1200 / 60Hz, 1280 × 1024 / 60Hz,
Storage medium	1 x 2,5''SATA HDD
Supported IP cameras	TVIP1156x, TVIP21560, TVIP41500, TVIP4x560, TVIP41660, TVIP615x0, TVIP6x560,
	TVIP82900
Synchronous playback	6
Total network throughput	(50/80) Mbits
(input/output)	
Total video channels	6
Video compression	H.264
EAN	4043158065916





Art.-Nr. TVVR36511T

Seite 3 von 4

	o surveillance 2MPx Wi-Fi mini tube camera
Alarming	Email
Aperture	F2.0
Automatic aperture control	No
Base event	Motion detection
Channel width	20 MHz
Colour	White
Compatible with	TVVR36xxx / TVVR33xxx / NVRxxxxx
Compatible with Secvest	Yes
Compatible with Smartvest	No
Compatible with wAppLoxx	Yes
DC voltage supply	12 V
Day/night switching	Auto / Manual / Schedule
Dimensions	(Ø x L) 69,7 x 171,4 mm
Dynamic range (WDR)	120 dB
Encryption	64/128-bit WEP / WPA/WPA2 / WPA-PSK/WPA2-PSK / WPS
Focal length	2,8 mm
Frequency range	2,4 - 2,4835 GHz
Gross weight	1,1 kg
Horizontal viewing angle	115 °
Housing material	Metal / Plastic
IP protection class	67
IR LEDs	Yes
IR range (up to)	30 m
IR swivel filter	Yes
Image enhancement	BLC / WDR
Image sensor	1/2.8" CMOS
Image settings	Brightness / Contrast / Saturation / Sharpness / Mirroring
Lens mount	M12
Loudspeaker	No
Max. humidity	95 %
Max. operating temperature	60 °C
Max. resolution @ frame rate	1920 x 1080 @ 25/30 fps
Microphone	No
Min. humidity	10
Min. operating temperature	-30 °C
Minimum illumination (IR)	0 lx
Minimum illumination	0,028 lx
(colour)	
Net weight	0,62 kg

Technical data - ABUS IP video surveillance 2MPx Wi-Fi mini tube camera

Art.-Nr. TVVR36511T

Seite 4 von 4

1x RJ-45 10/100 Mbit/s self-adaptive Ethernet Anschluss Network access TCP/IP / ICMP / HTTP / HTTPS / FTP / DHCP / DNS / DDNS / RTP / RTSP / RTCP / PPPoE / NTP / Network protocols UPnP / SMTP / IPv6 Noise reduction 3D DNR Number of users 32 DE / UK / FR / NL / DK / IT / PL / ES / SE OSD language Optical Wave Length 850 nm PoE standard 802.3af Power consumption 5,8 W Private zones 4 Recording modes Manual / time schedule / motion detection Resolution modes 1920 x 1080 / 1280 x 960 / 1280 x 720 @ 25/30 fps 11b: -90dBm / 11g: -75dBm / 11n: -74dBm Sensitivity Shutter speed 1/3s - 1/100.000s ABUS Link Station (iOS & Android) / IP Installer Software Storage medium MicroSD (max. 128GB) / NAS Internet Explorer, Edge, Chrome, Firefox, Safari Supported browsers IP Technology Transmission power 11b: 17 +/- 1,5dBm / 11g: 14 +/- 1,5dBm / 11n: 12,5 +/- 1,5dBm User levels 3 Video compression H.265 Plus / H.265 / H.264 Plus / H.264 / MJPEG IEEE802.11b/g/n / 11b @ 11Mbit/s / 11g @ 54Mbit/s / 11n @ 150Mbit/s WLAN network access Auto white balance (AWB) / incandescent lamp / warm light / natural light / White balance fluorescent lamp (Depending on installation) 20 - 50 m Wireless range EAN 4043158158977

Technical data - 2,5" Internal Hard Disk Drive with 1 TB Capacity

Connections	S-ATA
Dimensions	70 x 10 x 100 mm
Height	10 mm
Length	100 mm
Max. operating temperature	60 °C
Min. operating temperature	0 °C
Net weight	0,095 kg
Power consumption	1,4 W
Storage capacity	1.000
Width	70 mm
EAN	4043158063196

