

WLX Pro Wall Reader-Set Outdoor Intrusion white

Art.-Nr. ACSE00025

Seite 1 von 2



The wAppLoxx Pro Wall Reader ideally expands the digital access system's use cases with closing and locking technology. Electronic door openers, motorised locks, electronic barriers or gates: the wall reader reliably controls all important access points. The special added value: the wall reader can be accessed via app as part of the wAppLoxx Pro Plus system - allowing electronic garage doors or already installed motorised locks, for example, to be controlled intelligently at any time through the app - even while on the go. The high-quality, scratch-resistant glass front serves to identify access authorisations by reading in the locking medium and provides feedback to the user in the form of visual and acoustic signals.

Technologies

- Ideal for controlling electronic door and gate drives, door openers, lifts, barriers, rolling grilles, turnstiles
- Wall Reader RFID reader unit with encrypted bus connection to control unit (wAppLoxx Pro Bridge Box)
- High manipulation resistance thanks to separation of reading and control unit
- Encrypted AES 128-bit data transfer between wAppLoxx Pro Wall Reader, Bridge Box and Control
- Wall Reader: Elegant design in black with high-quality scratch-resistant glass in a robust metal housing
- External input on the Bridge Box allows a relay to be switched, e.g. for switches, buttons, etc.
- Other jumper settings, e.g. control of the 2nd relay in case of tampering, Wall Reader mute switching, pulse, delay, etc.
- Bus cable (5-core) already included in the scope of delivery with the reader (6m)
- Wall reader: Weather-resistant thanks to IP 67
- Arming and disarming intruder alarm systems

Technical data - WLX Pro Wall Reader-Set Outdoor Intrusion white

Article abbreviation	WLX-PRO-SET-WR-I-W-0
Closing media	Mifare DESfire EV1, Mifare DESfire EV2, Mifare Classic
Colour	white
Net weight	1.054 kg

WLX Pro Wall Reader-Set Outdoor Intrusion white

Art.-Nr. ACSE00025

Seite 2 von 2

Technical data - WLX Pro Wall Reader IP67 white

Areas of application	outdoor use
Colour	Frame silver / Glass white
Connections	BUS
Dimensions	119 x 97 x 20 mm
Height	70 mm
Housing material	genuine glass and metal frame
Max. Operating temperature inside	60 °C
Max. Operating temperature outside	60 °C
Min. operating temperature inside	-25 °C
Min. operating temperature outside	-25 °C
Net weight	0.56 kg
Protection class IP	67
EAN	4043158160642

Technical data - WLX Pro Bridge Box Intrusion

Areas of application	Indoor
Article abbreviation	WLX-PRO-BB-I
Colour	white
Connections	1 external input
DC power supply	3 A / 12 V
Dimensions	101 x 135 x 30 mm
Housing material	PVC
Max. Air humidity	80 %
Net weight	0.2 kg
Radio frequency	868.3 MHz
Radio range	up to 30 m indoors / free field nominal 100 m
WEEE group	09
EAN	4043158159134